

ABN 2/SS - Support bracket



0404460

<https://www.phoenixcontact.com/pc/products/0404460>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Double support bracket, insulating material, optionally for use with 3 x 10 mm or 6 x 6 mm busbar, height in closed state: 39 mm

Commercial data

Item number	0404460
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BE7113
Catalog page	Page 552 (C-3-2019)
GTIN	4017918001902
Weight per piece (including packing)	5.52 g
Weight per piece (excluding packing)	5.32 g
Customs tariff number	39269097
Country of origin	PL

ABN 2/SS - Support bracket



0404460

<https://www.phoenixcontact.com/pc/products/0404460>

Technical data


Product properties

Product type	Support bracket
Number of positions	2.00

Electrical properties

Nominal current I _N	0 A
--------------------------------	-----

Dimensions

Dimensional drawing	
Width	10 mm
Height	47 mm
Depth	39 mm
Length	47 mm
Diameter	4.5 mm

Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed
Components	free from silicone and halogen

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C

ABN 2/SS - Support bracket

0404460

<https://www.phoenixcontact.com/pc/products/0404460>



Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	Direct mounting
---------------	-----------------

ABN 2/SS - Support bracket


0404460

<https://www.phoenixcontact.com/pc/products/0404460>



Drawings

Dimensional drawing



ABN 2/SS - Support bracket



0404460

<https://www.phoenixcontact.com/pc/products/0404460>

Classifications

ECLASS

ECLASS-11.0	27400607
ECLASS-12.0	27400607
ECLASS-13.0	27400607

ETIM

ETIM 9.0	EC001166
----------	----------

UNSPSC

UNSPSC 21.0	39121700
-------------	----------

ABN 2/SS - Support bracket



0404460
<https://www.phoenixcontact.com/pc/products/0404460>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com