

AKG 4 GNYE-EX - Connection terminal block



0421045

<https://www.phoenixcontact.com/in/products/0421045>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connection terminal block, nom. voltage: 300 V, nominal current: 32 A, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.5 mm² - 6 mm², mounting: Neutral busbar, color: green-yellow

Commercial data

Item number	0421045
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE7
Product key	BE7331
Catalog page	Page 554 (C-3-2019)
GTIN	4017918001940
Weight per piece (including packing)	5.522 g
Weight per piece (excluding packing)	4.71 g
Customs tariff number	85369010
Country of origin	IN

AKG 4 GNYE-EX - Connection terminal block



0421045

<https://www.phoenixcontact.com/in/products/0421045>

Technical data

Product properties

Product type	Installation terminal block
Number of connections	1
Number of rows	1

Data management status

Article revision	09
------------------	----

Electrical properties

Maximum load current	41 A
Maximum power dissipation for nominal condition	1.02 W
Nominal current I_N	32 A

Connection data

Nominal cross section	4 mm ²
Maximum load current	41 A

Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	16 mm
Conductor cross section rigid	0.5 mm ² ... 6 mm ²
Cross section AWG	20 ... 10 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 4 mm ²
Conductor cross section, flexible [AWG]	20 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ²
2 conductors with same cross section, solid	0.5 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible	0.5 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.5 mm ² ... 2.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 2.5 mm ²
Nominal current	32 A
Maximum load current	41 A (with 6 mm ² conductor cross section)
Nominal voltage	300 V
Nominal cross section	4 mm ²

Ex data

Rated data (ATEX/IECEx)

Identification	Ex II 2 G Ex eb IIC Gb
Operating temperature range	-60 °C ... 125 °C

AKG 4 GNYE-EX - Connection terminal block



0421045

<https://www.phoenixcontact.com/in/products/0421045>

Ex-certified accessories	0404415 AB/SS-EX
	0402006 NLS-CU 3/10 SN 2000MM
	1212588 SF-SL 0,8X4,0-100 S-VDE
Ex temperature increase	25 K (32 A / 4 mm ²)
output	(Permanent)

Ex level General

Rated current	32 A
Maximum load current	41 A
Contact resistance	0.08 mΩ

Ex connection data General

Torque range	1.5 Nm ... 1.8 Nm
Nominal cross section	4 mm ²
Rated cross section AWG	12
Connection capacity rigid	0.5 mm ² ... 6 mm ²
Connection capacity AWG	20 ... 10
Connection capacity flexible	0.5 mm ² ... 4 mm ²
Connection capacity AWG	20 ... 12
2 conductors with same cross section, solid	0.5 mm ² ... 2.5 mm ²
2 conductors with the same cross-section AWG rigid	20 ... 14
2 conductors with same cross section, stranded	0.5 mm ² ... 2.5 mm ²
2 conductors with the same cross-section AWG flexible	20 ... 14

Dimensions

Dimensional drawing	
Width	7 mm
Height	23.4 mm
Depth	24 mm
Length	23.4 mm

Material specifications

Color	green-yellow
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Electrical tests

AKG 4 GNYE-EX - Connection terminal block



0421045

<https://www.phoenixcontact.com/in/products/0421045>

Result	Test passed
--------	-------------

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

Result	Test passed
--------	-------------

Environmental and real-life conditions

Needle-flame test

Result	Test passed
--------	-------------

Ambient conditions


Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting


Mounting type	Neutral busbar
---------------	----------------

Drawings

Dimensional drawing



Dimensional drawing



AKG 4 GNYE-EX - Connection terminal block



0421045

<https://www.phoenixcontact.com/in/products/0421045>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/0421045>

	cUL Recognized Approval ID: E192998			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	-	-	22 - 12	22 - 12

	EAC Ex Approval ID: RU C-DE.HA91.B.00066
---	--

	IECEx Approval ID: IECExKIWA14.0005U
---	--

	UL Recognized Approval ID: E192998			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	-	-	22 - 12	-

	ATEX Approval ID: KIWA14ATEX0011U			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Only flexible conductors	-	32 A	-	0.5 - 4
Only rigid conductors	-	41 A	-	0.5 - 6

	CCC Approval ID: 2020322313000874
---	---

cULus Recognized

AKG 4 GNYE-EX - Connection terminal block



0421045

<https://www.phoenixcontact.com/in/products/0421045>

Classifications

ECLASS

ECLASS-11.0	27141146
ECLASS-12.0	27141146
ECLASS-13.0	27250116

ETIM

ETIM 9.0	EC000001
----------	----------

UNSPSC

UNSPSC 21.0	31162900
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%