

# Specifications



## Eaton 051803

Eaton Moeller® series DILEM Contactor, 220 V 50 Hz, 240 V 60 Hz, 4 pole, 380 V 400 V, 4 kW, Screw terminals, AC operation

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILEM Mini contactor
<b>CATALOG NUMBER</b>	051803
<b>MODEL CODE</b>	DILEM4(220V50HZ,240V60HZ)
<b>EAN</b>	4015080518037
<b>PRODUCT LENGTH/DEPTH</b>	52 mm
<b>PRODUCT HEIGHT</b>	58 mm
<b>PRODUCT WIDTH</b>	45 mm
<b>PRODUCT WEIGHT</b>	0.17 kg
<b>CERTIFICATIONS</b>	IEC/EN 60947-4-1 CE UL 508 IEC/EN 60947 UL Category Control No.: NLDX UL CSA-C22.2 No. 14-05 CSA File No.: 012528 CSA VDE 0660 UL File No.: E29096 CSA Class No.: 3211-04
<b>CATALOG NOTES</b>	Also tested according to AC-3e.
<b>GLOBAL CATALOG</b>	051803

## Product specifications

<b>NUMBER OF POLES</b>	Four-pole
<b>FEATURES</b>	Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.

## Resources

### CATALOGS

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Product Range Catalog](#)  
[Switching and protecting motors](#)

[eaton-contactors-short-time-loading-dilm-characteristic-curve.eps](#)

### CHARACTERISTIC CURVE

[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

### DECLARATIONS OF CONFORMITY

[DA-DC-00004812.pdf](#)

[DA-DC-00004788.pdf](#)

### DRAWINGS

[eaton-contactors-diler-dimensions-004.eps](#)

[eaton-contactors-diler-dimensions-005.eps](#)

[eaton-contactors-dilem-dimensions.eps](#)

[eaton-tripping-devices-mounting-diler-contactor-relay-symbol.eps](#)

### ECAD MODEL

[ETN.051803.edz](#)

### INSTALLATION INSTRUCTIONS

[IL03407009Z](#)

### MCAD MODEL

[DA-CD-dil\\_em](#)

[DA-CS-dil\\_em](#)

### SYSTEM OVERVIEW

[eaton-contactors-accessory-dilem-system-overview.eps](#)

### WIRING DIAGRAMS

[eaton-contactors-contact-dilem-wiring-diagram.eps](#)

<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>OPERATING FREQUENCY</b>	9000 mechanical Operations/h
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V AC
<b>UTILIZATION CATEGORY</b>	AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching
<b>CONNECTION</b>	Screw terminals
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	50 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C

**AMBIENT OPERATING**

**TEMPERATURE** 40 °C  
**(ENCLOSED) - MAX**

**AMBIENT OPERATING**

**TEMPERATURE** -25 °C  
**(ENCLOSED) - MIN**

**AMBIENT STORAGE**

**TEMPERATURE - MAX** 80 °C

**AMBIENT STORAGE**

**TEMPERATURE - MIN** -40 °C

**ASSIGNED MOTOR**

**POWER AT 115/120 V, 60 HZ, 1-PHASE** 0.5 HP

**ASSIGNED MOTOR**

**POWER AT 200/208 V, 60 HZ, 3-PHASE** 2 HP

**ASSIGNED MOTOR**

**POWER AT 230/240 V, 60 HZ, 1-PHASE** 1.5 HP

**ASSIGNED MOTOR**

**POWER AT 230/240 V, 60 HZ, 3-PHASE** 3 HP

**ASSIGNED MOTOR**

**POWER AT 460/480 V, 60 HZ, 3-PHASE** 5 HP

**ASSIGNED MOTOR**

**POWER AT 575/600 V, 60 HZ, 3-PHASE** 5 HP

**CONVENTIONAL**

**THERMAL CURRENT ITH (1-POLE, ENCLOSED)** 50 A

**CONVENTIONAL**

**THERMAL CURRENT ITH (3-POLE, ENCLOSED)** 16 A

**CONVENTIONAL**

**THERMAL CURRENT ITH AT 55°C (3-POLE, OPEN)** 19 A

**CONVENTIONAL**

**THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)** 10 A

**CONVENTIONAL**

**THERMAL CURRENT ITH OF MAIN CONTACTS (1-POLE, OPEN)** 60 A

**EQUIPMENT HEAT**

**DISSIPATION, CURRENT-DEPENDENT PVID** 9.56 W

**HEAT DISSIPATION**

**CAPACITY PDISS** 0 W

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	2.39 W
<b>SWITCHING TIME (AC OPERATED, N/O, WITH AUXILIARY CONTACT MODULE, CLOSING DELAY)</b>	45 ms
<b>APPLICATION</b>	Mini Contactors for Motors and Resistive Loads
<b>PRODUCT CATEGORY</b>	Contactors
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
<b>ARCING TIME</b>	12 ms at 690 V AC
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>SCREWDRIVER SIZE</b>	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
<b>VOLTAGE TYPE</b>	AC
<b>DEGREE OF PROTECTION</b>	IP20
<b>MOUNTING POSITION</b>	As required (except vertical with terminals A1/A2 at the bottom)
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT</b>	0
<b>NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)</b>	4
<b>RATED BREAKING CAPACITY AT 220/230 V</b>	90 A
<b>RATED BREAKING CAPACITY AT 380/400 V</b>	90 A
<b>RATED BREAKING CAPACITY AT 500 V</b>	64 A

<b>RATED BREAKING CAPACITY AT 660/690 V</b>	42 A
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT AC, 50</b>	220 V
<b>Hz - MAX</b>	
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT AC, 50</b>	220 V
<b>Hz - MIN</b>	
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT AC, 60</b>	240 V
<b>Hz - MAX</b>	
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT AC, 60</b>	240 V
<b>Hz - MIN</b>	
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONTROL CIRCUIT RELIABILITY</b>	< 2 $\lambda$ , < 1 failure at 100,000,000 Operations (at $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
<b>DUTY FACTOR</b>	100 %
<b>CHANGEOVER TIME</b>	16 - 21 ms
<b>LIFESPAN, MECHANICAL</b>	20,000,000 Operations 150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A) 200,000 Operations (at 240 V, AC-15) 7,000,000 Operations (Coil 50/60 Hz)
<b>PICK-UP VOLTAGE</b>	1.1 V AC x $U_c$ (voltage tolerance - dual frequency coil 50/60 Hz) 0.8 - 1.1 V AC x $U_c$ (voltage tolerance - single-voltage coil 50 Hz and dual-voltage coil 50 Hz, 60 Hz)
<b>POWER CONSUMPTION, PICK-UP, 50 Hz</b>	25 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz 22 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
<b>SAFE ISOLATION</b>	300 V AC, Between the contacts, According to EN 61140 300 V AC, Between coil and auxiliary contacts, According to EN 61140 300 V AC, Between auxiliary contacts,

	According to EN 61140 300 V AC, Between coil and contacts, According to EN 61140
<b>POWER CONSUMPTION, PICK-UP, 60 Hz</b>	22 W, AC, Single-frequency coil 50 Hz and Dual- frequency coil 50/60 Hz 25 VA, AC, Single- frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
<b>SCREW SIZE</b>	M3.5, Terminal screw
<b>POWER CONSUMPTION, SEALING, 50 Hz</b>	1.8 W, AC, Single- frequency coil 50 Hz and Dual-frequency coil 50/60 Hz 4.6 VA, AC, Single- frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
<b>POWER CONSUMPTION, SEALING, 60 Hz</b>	1.8 W, AC, Single- frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
<b>RATED OPERATIONAL CURRENT (IE)</b>	2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series) 1.5 A at 100 V, DC L/R ≤ 15 ms (with 3 contacts in series) 0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series)
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	2 x (0.75 - 1.5) mm <sup>2</sup> 1 x (0.75 - 1.5) mm <sup>2</sup>
<b>SHOCK RESISTANCE</b>	20 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 20 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 10 g, N/O main contact, Basic unit with auxiliary contact module,

	Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 2.5) mm <sup>2</sup>
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	18 - 14
<b>SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)</b>	15 A, Maximum motor rating (UL/CSA)
<b>TIGHTENING TORQUE</b>	1.2 Nm, Screw terminals
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT DC - MAX</b>	0 V
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT DC - MIN</b>	0 V
<b>RATED INSULATION VOLTAGE (UI)</b>	690 V
<b>RATED MAKING CAPACITY UP TO 440 V (COS PHI TO IEC/EN 60947)</b>	110 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V</b>	22 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>	6 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>	3 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V</b>	1.5 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V</b>	9 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V</b>	9 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V</b>	9 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 500 V** 6.4 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 660 V, 690 V** 4.8 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V** 6.6 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 400 V** 6.6 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 440 V** 6.6 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 500 V** 5 A

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 660 V, 690 V** 3.4 A

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 110 V** 20 A

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 12 V** 20 A

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 220 V** 20 A

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 24 V** 20 A

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 60 V** 20 A

**RATED OPERATIONAL**

**CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)** 22 A

**RATED OPERATIONAL**

**POWER AT AC-3, 240 V, 50 HZ** 2.5 kW

**RATED OPERATIONAL**

**POWER AT AC-3, 380/400 V, 50 HZ** 4 kW

**RATED OPERATIONAL**

**POWER AT AC-3, 415 V, 50 HZ** 4.3 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 220/230 V** 1.5 kW

**V, 50 Hz****RATED OPERATIONAL**

**POWER AT AC-4, 240 V, 50 Hz** 1.8 kW

**V, 50 Hz****RATED OPERATIONAL**

**POWER AT AC-4, 380/400 V, 50 Hz** 3 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 415 V, 50 Hz** 3.1 kW

**V, 50 Hz****RATED OPERATIONAL**

**POWER AT AC-4, 440 V, 50 Hz** 3.3 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 500 V, 50 Hz** 3 kW

**V, 50 Hz****RATED OPERATIONAL**

**POWER AT AC-4, 660/690 V, 50 Hz** 3 kW

**RATED OPERATIONAL**

**POWER (NEMA)** 3.7 kW

**RATED OPERATIONAL**

**VOLTAGE (UE) AT AC - MAX** 690 V

**RESISTANCE PER POLE** 9.18 mΩ

**STATIC HEAT**

**DISSIPATION, NON-CURRENT-DEPENDENT PVS** 1.8 W

**STRIPPING LENGTH (MAIN CABLE)** 8 mm

**SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX** 21 ms

**SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN** 14 ms

**SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX** 18 ms

**SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN** 8 ms

**SHORT-CIRCUIT CURRENT RATING (BASIC RATING)** 45 A, max. Fuse, SCCR (UL/CSA)

5 kA, SCCR (UL/CSA)

**SHORT-CIRCUIT PROTECTION**  
6 A gG/gL, Max. Fuse 500V,  
Auxiliary contacts, Short-circuit rating without  
welding  
PKZM0-4, Maximum  
overcurrent protective  
device, Short-circuit  
protection only, Auxiliary  
contacts, Short-circuit  
rating without welding  
10 A fast, Max. Fuse 500V,  
Auxiliary contacts, Short-circuit rating without  
welding

**SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 500 V**  
20 A gG/gL

**SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 500 V**  
10 A gG/gL

**CONVENTIONAL THERMAL CURRENT ITH AT 40°C (3-POLE, OPEN)**  
22 A

**CONVENTIONAL THERMAL CURRENT ITH AT 50°C (3-POLE, OPEN)**  
20 A

**RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ**  
4.6 kW

**RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ**  
4 kW

**RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ**  
4 kW

**ACTUATING VOLTAGE** 220 V 50 Hz, 240 V 60 Hz

**ALTITUDE** Max. 2000 m

**OPERATING VOLTAGE AT AC, 50 HZ - MIN** 24 V

**OPERATING VOLTAGE AT AC, 50 HZ - MAX** 690 V

**OPERATING VOLTAGE AT AC, 60 HZ - MIN** 24 V

**OPERATING VOLTAGE AT AC, 60 HZ - MAX** 690 V

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

