

Feed-through terminal block - REKORD KER-EX - 0551054

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through terminal block, nom. voltage: 800 V, nominal current: 76 A, connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 16 mm², AWG: 20 - 6, width: 10.2 mm, color: light brown, mounting type: NS 32

Figure not currently available

RoHS

Key Commercial Data

Packing unit	50 STK
GTIN	 4 017918 002886
GTIN	4017918002886

Technical data

General

Number of levels	1
Number of connections	2
Color	light brown
Material	Ceramics
Flammability rating according to UL 94	V0
Maximum load current	76 A
Nominal current I _N	76 A
Nominal voltage U _N	800 V
Open side panel	Yes

Dimensions

Width	10.2 mm
Length	47.4 mm
Height NS 32	58.6 mm

Connection data

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²

Feed-through terminal block - REKORD KER-EX - 0551054

Technical data

Connection data

Conductor cross section solid max.	16 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	6
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	10 mm ²
Min. AWG conductor cross section, flexible	20
Max. AWG conductor cross section, flexible	8
Stripping length	11 mm
Screw thread	M 4

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>