

0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 500 V, nominal current: 17.5 A, number of connections: 2, connection method: Screw connection, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 1.5 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: orange

Commercial data

Item number	0719016
Packing unit	50 pc
Minimum order quantity	1 pc
Product key	BE1211
GTIN	4017918591410
Weight per piece (including packing)	5.77 g
Weight per piece (excluding packing)	5.77 g
Customs tariff number	85369010
Country of origin	CN

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Technical data

Product properties

Product type	Feed-through terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	0.56 W

Connection data

Number of connections per level	2
Nominal cross section	1.5 mm ²

Level 1 above 1 below 1

Screw thread	M2
Tightening torque	0.22 ... 0.25 Nm
Stripping length	7 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.14 mm ² ... 1.5 mm ²
Cross section AWG	26 ... 16 (converted acc. to IEC)
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section, flexible [AWG]	26 ... 16 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 0.75 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 0.75 mm ²
2 conductors with same cross section, solid	0.14 mm ² ... 0.75 mm ²
2 conductors with same cross section, flexible	0.14 mm ² ... 0.75 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 0.34 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ²
Nominal current	17.5 A
Maximum load current	17.5 A (with 1.5 mm ² conductor cross section)
Nominal voltage	500 V
Nominal cross section	1.5 mm ²

Ex data

Rated data (ATEX/IECEx)

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Identification	II 2 GD Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	3001022 D-UK 2,5
	1205037 SZS 0,4X2,5 VDE
	1201442 E/UK
List of bridges	Fixed bridge / FBRN 10-4 N / 3001624
	Fixed bridge / FBRN 20-4 N / 3001637
Bridge data	15.5 A / 1.5 mm ²
Ex temperature increase	40 K (17.5 A / 1.5 mm ²)
Rated voltage	352 V
for bridging with bridge	352 V
- At bridging between non-adjacent terminal blocks	69 V
Rated insulation voltage	320 V
output	(Permanent)

Ex level General

Rated current	15.5 A
Maximum load current	15.5 A
Contact resistance	0.45 mΩ

Ex connection data General

Torque range	0.22 Nm ... 0.25 Nm
Nominal cross section	1.5 mm ²
Rated cross section AWG	16
Connection capacity rigid	0.14 mm ² ... 1.5 mm ²
Connection capacity AWG	26 ... 16
Connection capacity flexible	0.14 mm ² ... 1.5 mm ²
Connection capacity AWG	26 ... 16
2 conductors with same cross section, solid	0.14 mm ² ... 0.75 mm ²
2 conductors with the same cross-section AWG rigid	26 ... 18
2 conductors with same cross section, stranded	0.14 mm ² ... 0.75 mm ²
2 conductors with the same cross-section AWG flexible	26 ... 18

Dimensions

Width	4.2 mm
-------	--------

Material specifications

Color	orange
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	7.3 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 1.5 mm ²	0.18 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.14 mm ² / 0.2 kg
	1.5 mm ² / 0.4 kg
Result	Test passed

Environmental and real-life conditions

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Drawings

Circuit diagram



UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/0719016>

DNV

Approval ID: TAE00001CT



EAC

Approval ID: RU C-DE.BL08.B.00534



cULus Recognized

Approval ID: E60425

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	300 V	15 A	30 - 14	-
Use group C				
	300 V	15 A	30 - 14	-
Use group F				
	500 V	15 A	30 - 14	-
Use group D				
	600 V	5 A	30 - 14	-



BV

Approval ID: 07774/E0 BV



ATEX

Approval ID: KEMA98ATEX1651U

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Type examination certificate	352 V	17 A	-	0.14 - 1.5



EAC Ex

Approval ID: RU C-DE.HA91.B.00066



IECEx

Approval ID: IECEx KEM 06.0034U

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	352 V	17 A	-	0.14 - 1.5

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>



CCC

Approval ID: 2020322313000623

UK 1,5 N OG - Feed-through terminal block



0719016

<https://www.phoenixcontact.com/pc/products/0719016>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UK 1,5 N OG - Feed-through terminal block



0719016
<https://www.phoenixcontact.com/pc/products/0719016>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com