

# WML 7,5 (13X13)R - Wire-wrap label



0800074

<https://www.phoenixcontact.com/pc/products/0800074>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



## Your advantages

- For indoor and outdoor applications: high resistance to dirt and abrasion due to the protective laminate
- Firmly defined positioning of labels thanks to the adhesive system
- Broad diameter range with many different applications inside and outside the control cabinet
- The wrap-around labels do not create any additional volume, so the cable can also be pulled through cable ducts, for example
- Quick and easy handling
- For cylindrical objects, single wires, and cables

## Commercial data

Item number	0800074
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BG2311
Catalog page	Page 217 (C-3-2019)
GTIN	4046356562072
Weight per piece (including packing)	545 g
Weight per piece (excluding packing)	545 g
Customs tariff number	39199080
Country of origin	DE

# WML 7,5 (13X13)R - Wire-wrap label



0800074

<https://www.phoenixcontact.com/pc/products/0800074>

## Technical data

### Product properties

Product type	Conductor marking
Type	Label

### Marking

Number of individual labels	4000
Number of individual labels per row	5
Identification technology	Thermal transfer for rolls

### Dimensions

Width	12.7 mm
Length	36.5 mm

### External dimensions

Outside diameter	3 mm ... 7.5 mm
------------------	-----------------

### Material specifications

Foil strength	80 µm
Adhesive strength	21 µm
Adhesive	Acrylic
Color	white
Material	PVC
Components	Silicone-free

### Cable/line

External cable diameter	≤ 7.60 mm
	4 mm ... 7.6 mm

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

#### Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

# WML 7,5 (13X13)R - Wire-wrap label



0800074

<https://www.phoenixcontact.com/pc/products/0800074>

## UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

## Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed

## Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Acetone (99 %) [CAS No. 67-64-1]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
IRM 901	Test passed
IRM 902	Test passed

## Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

## Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	> 0 °C

# WML 7,5 (13X13)R - Wire-wrap label



0800074

<https://www.phoenixcontact.com/pc/products/0800074>

Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Mounting

Mounting type	adhesive
---------------	----------


# WML 7,5 (13X13)R - Wire-wrap label

0800074

<https://www.phoenixcontact.com/pc/products/0800074>



## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/0800074>



**UL Recognized**

Approval ID: MH48542

# WML 7,5 (13X13)R - Wire-wrap label

0800074

<https://www.phoenixcontact.com/pc/products/0800074>



## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

# WML 7,5 (13X13)R - Wire-wrap label



0800074

<https://www.phoenixcontact.com/pc/products/0800074>

## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)