

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 6.2 mm, Number of individual labels: 1000, text field height: 6.15 mm, text field width: 5.15 mm

Your advantages

- Unlabeled marking strips can be custom-labeled with a plotter or by hand
- Other pitches available on request
- The ZBF zack marker strip system with flat marker groove is a marking solution for modular terminal blocks and electronics modules
- The multi-section marking strips are easy to fit and can be easily separated if required

Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0808736             |
| Packing unit                         | 100 pc              |
| Minimum order quantity               | 100 pc              |
| Sales key                            | BG05                |
| Product key                          | BG2112              |
| Catalog page                         | Page 127 (C-3-2019) |
| GTIN                                 | 4017918180270       |
| Weight per piece (including packing) | 0.416 g             |
| Weight per piece (excluding packing) | 0.411 g             |
| Customs tariff number                | 39269097            |
| Country of origin                    | DE                  |

## Technical data

### Product properties

|              |                  |
|--------------|------------------|
| Product type | Terminal marking |
| Pitch        | 6.2 mm           |
| Type         | flat             |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 00 |
|------------------|----|

### Marking

|                                     |      |
|-------------------------------------|------|
| Number of individual labels         | 1000 |
| Number of individual labels per row | 10   |
| Number of marker strips             | 100  |

### Dimensions

|                   |         |
|-------------------|---------|
| Width             | 6 mm    |
| Text field width  | 5.15 mm |
| Text field height | 6.15 mm |
| Pitch             | 6.2 mm  |

### Material specifications

|                                        |                                |
|----------------------------------------|--------------------------------|
| Color                                  | white (RAL 9010)               |
| Material                               | PA                             |
| Flammability rating according to UL 94 | V2                             |
| Components                             | free from silicone and halogen |

### Environmental and real-life conditions

#### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

#### Wipe resistance of inscriptions

|               |                                                |
|---------------|------------------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07            |
|               | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |

#### Ambient conditions

|                                                     |                   |
|-----------------------------------------------------|-------------------|
| Ambient temperature (operation)                     | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C             |
| Recommended humidity (storage/transport)            | 50 %              |

### Standards and regulations


|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

### Mounting

|               |          |
|---------------|----------|
| Mounting type | latching |
|---------------|----------|

Drawings

Schematic diagram



# ZBF 6/WH-100:UNBEDRUCKT - Zack Marker strip, flat



0808736

<https://www.phoenixcontact.com/us/products/0808736>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000761 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Environmental product compliance

EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|