

0816443

https://www.phoenixcontact.com/us/products/0816443

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, Roll, yellow, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, perforated, mounting type: snap into universal marker groove, snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 6.4 x 5.15 mm, Number of individual labels: 19000

### Your advantages

- The TMT labeling range includes markers for all products with tall and flat marker grooves
- · The markers that are supplied in roll format can be labeled quickly and cost-effectively using THERMOMARK printers
- · Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- · When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- · The perforated marking strips are easy to separate and can be easily fitted using the tool supplied
- Labeling service: Phoenix Contact can custom-label all TMT ... markers in accordance with your requirements

### Commercial data

| Item number                          | 0816443                        |
|--------------------------------------|--------------------------------|
| Packing unit                         | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BG11                           |
| Product key                          | BG2111                         |
| Catalog page                         | Page 95 (C-5-2013)             |
| GTIN                                 | 4046356107228                  |
| Weight per piece (including packing) | 535.81 g                       |
| Weight per piece (excluding packing) | 447.09 g                       |
| Customs tariff number                | 39269092                       |
| Country of origin                    | DE                             |



0816443

https://www.phoenixcontact.com/us/products/0816443

### Technical data

### Product properties

| Product type                        | Terminal marking |
|-------------------------------------|------------------|
| Pitch                               | 5.2 mm           |
| Туре                                | flat             |
| Marking                             |                  |
| Number of individual labels         | 19000            |
| Number of individual labels per row | 19               |

### **Dimensions**

| Width  | 5.15 mm |
|--------|---------|
| Height | 6.4 mm  |
| Length | 6.4 mm  |
| Pitch  | 5.2 mm  |

### Material specifications

| RoHS compliant        | yes                            |
|-----------------------|--------------------------------|
| Foil strength         | 175 μm                         |
| Color                 | yellow                         |
| Material              | Polyester                      |
| Base element material | Polyester foil                 |
| Components            | free from silicone and halogen |

### Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| Test passed                                    |
|--|
|  |
| ISO 4892-2:2013-03 (following)                 |
| Test passed                                    |
| 96 h   |
|  |
| DIN EN 61010-1 (VDE 0411-1):2011-07            |
| DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Test passed                                    |
| Test passed                                    |
| Test passed                                    |
|  |

Testing in a condensation changing climate in the presence of sulfur dioxide

| Specification | DIN 50018:2013-05 |
|---------------|-------------------|



0816443

https://www.phoenixcontact.com/us/products/0816443

| Result  | Test passed                       |
|---|-----------------------------------|
| Climate level                                       | AHT 1.0 S                         |
| Cycles  | 2                                 |
| Salt spray test                                     |                                   |
| Specification                                       | DIN EN 60068-2-11:2000-02         |
| Result  | Test passed                       |
| Ambient conditions  Ambient temperature (operation) | -40 °C 120 °C                     |
| Recommended storage conditions                      | 23 °C / 50 % relative humidity    |
| Shelf life  | 2 years                           |
| Standards and regulations                           |                                   |
| Wipe resistance                                     | DIN EN 61010-1 (VDE 0411-1)       |
| Mounting  |                                   |
| Mounting type                                       | snap into universal marker groove |



0816443

https://www.phoenixcontact.com/us/products/0816443

# Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%



0816443

https://www.phoenixcontact.com/us/products/0816443

#### Accessories

#### THERMOMARK ROLLMASTER 300 - Thermal transfer printer

0804501

https://www.phoenixcontact.com/us/products/0804501



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m

### THERMOMARK ROLLMASTER 600 - Thermal transfer printer

0804663

https://www.phoenixcontact.com/us/products/0804663



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m



0816443

https://www.phoenixcontact.com/us/products/0816443

#### THERMOMARK ROLL 2.0 - Thermal transfer printer

1085260

https://www.phoenixcontact.com/us/products/1085260



Thermal transfer printer for material off the roll, incl. Euro/US power cable and USB cable. Operating instructions printed in German and English. 1 roll of labels EML (20x8)R white = 1000 labels, ink ribbon = 50 m

#### THERMOMARK ROLL - Thermal transfer printer

5146477

https://www.phoenixcontact.com/us/products/5146477



Thermal transfer printer, 300 dpi, incl. European power cable, US power cable, and USB cable. DVD with CLIP PROJECT advanced planning and marking software, user manuals in various languages, Windows<sup>®</sup> printer driver, and firmware. German/English user manual in DIN A5 format, EML (20x8)R roll of labels, white, with 1000 labels, and ink ribbon: 50 m



0816443

https://www.phoenixcontact.com/us/products/0816443

#### THERMOMARK X1.2 - Thermal transfer printer

5146231

https://www.phoenixcontact.com/us/products/5146231



Thermal transfer printer, weight: 10 kg, length:  $0.446 \, \text{m}$ , width:  $242 \, \text{mm}$ , height:  $274 \, \text{mm}$ , color: gray

#### THERMOMARK-RIBBON 110-WMTB HF - Ink ribbon

5148007

https://www.phoenixcontact.com/us/products/5148007



Ink ribbon, for roll printer for printing product groups WMTB HF..., WMS-2 HF..., TMT..., EMT..., EMLF..., PML-..., length: 300 m, roll length: 300 m, width: 110 mm, color: black



0816443

https://www.phoenixcontact.com/us/products/0816443

### TMT TOOL - Locking tool

0816650

https://www.phoenixcontact.com/us/products/0816650



Snap-in tool, makes it easier to snap the TMT marker into the flat marker groove

### THERMOMARK E.300 US - Thermal transfer printer

1287021

https://www.phoenixcontact.com/us/products/1287021



Thermal transfer printer for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.



0816443

https://www.phoenixcontact.com/us/products/0816443

#### THERMOMARK E.600 US - Thermal transfer printer

1287029

https://www.phoenixcontact.com/us/products/1287029



Thermal transfer printer for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

### THERMOMARK E.300 D US - Thermal transfer printer

1287033

https://www.phoenixcontact.com/us/products/1287033



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.



0816443

https://www.phoenixcontact.com/us/products/0816443

### THERMOMARK E.600 D US - Thermal transfer printer

1287040

https://www.phoenixcontact.com/us/products/1287040



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com