0817701

https://www.phoenixcontact.com/us/products/0817701

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, Sheet, red, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 12 mm, Number of individual labels: 40, text field height: 10.5 mm, text field width: 11.45 mm

Your advantages

- The markers, which are supplied in uniform sheets, can be printed onto quickly and easily using the BLUEMARK printing systems
- The UC-TM ... UniCard labeling range includes terminal markers for Phoenix Contact products with tall marker grooves
- · The multi-section marking strips are easy to fit and can be easily separated if required
- The markers support multi-line labeling
- · The sheets provide space for including function texts
- · Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications

Commercial data

Item number	0817701
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG06
Product key	BG2117
Catalog page	Page 111 (C-3-2019)
GTIN	4046356108171
Weight per piece (including packing)	12.63 g
Weight per piece (excluding packing)	9 g
Customs tariff number	39269097
Country of origin	PL

0817701

https://www.phoenixcontact.com/us/products/0817701



Technical data

Product properties

Product type	Terminal marking
Pitch	12 mm
Туре	high
Data management status	
Article revision	04
Marking	
Number of individual labels	40
Number of individual labels per row	5
Identification technology	UV LED technology
imensions	
Width	12 mm
Text field width	11.45 mm
Text field height	10.50 mm
Pitch	12 mm
laterial specifications	
RoHS compliant	294

RoHS compliant	yes
Color	red (RAL 3001)
Material	PA
Flammability rating according to UL 94	V2
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 2
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish	
Result	Test passed
UV resistance	
Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
Wipe resistance of inscriptions	
Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed



0817701

https://www.phoenixcontact.com/us/products/0817701

n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Festing in a condensation changing climate in the presence of sulfu	ur dioxide
Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2
Salt spray test	
Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Ambient conditions	
Ambient temperature (operation)	-40 °C 120 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
andards and regulations	
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
punting	
Mounting type	latching

0817701

https://www.phoenixcontact.com/us/products/0817701



Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

ETIM 9.0	EC000761
UNSPSC	
UNSPSC 21.0	39131500

0817701

https://www.phoenixcontact.com/us/products/0817701



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com