

0824594

https://www.phoenixcontact.com/us/products/0824594

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, can be ordered: by sheet, violet, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

Your advantages

- The UC-TM ... UniCard labeling range includes markers for products with tall marker grooves
- · Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications
- · The multi-section marking strips are easy to fit and can be easily separated if required
- · The sheets provide space for including function texts
- The markers support multi-line labeling
- The format automatically ensures printing with a high degree of positioning accuracy

Commercial data

Item number	0824594
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BG24
Product key	BG8117
Catalog page	Page 59 (C-5-2013)
GTIN	4046356359238
Weight per piece (including packing)	11.58 g
Weight per piece (excluding packing)	8.7 g
Customs tariff number	49119900
Country of origin	PL



0824594

https://www.phoenixcontact.com/us/products/0824594

Technical data

Product properties

Product type	Labeled terminal marker
Pitch	6.2 mm
Туре	high
Marking	
Number of individual labels	80
Number of individual labels per row	10
Identification technology	UV LED technology

Mounting

Material specifications

RoHS compliant	yes
Color	violet
Material	PA
Flammability rating according to UL 94	V2
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 2
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
V resistance	
Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
mbient conditions	
mbient conditions Ambient temperature (operation)	-40 °C 120 °C

Dimensions

Width	6 mm
Pitch	6.2 mm

Standards and regulations


Wipe resistance	DIN EN 61010-1 (VDE 0411-1)



0824594

https://www.phoenixcontact.com/us/products/0824594

Drawings



① Horizontal

② Vertical



0824594

https://www.phoenixcontact.com/us/products/0824594

Classifications

	ECLASS-11.0	27281101
Εī	ГІМ	
	ETIM 8.0	EC000761
U	NSPSC	
	UNSPSC 21.0	39131500



0824594

https://www.phoenixcontact.com/us/products/0824594

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com