

SK 5,0 REEL P7,5 WH CUS - Marker card

0825131

<https://www.phoenixcontact.com/us/products/0825131>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker card, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, for terminal block width: 7.5 mm



Your advantages

- Labeling service: Phoenix Contact can custom-label all SK ... markers in accordance with your requirements
- The SK labeling range offers self-adhesive marker strips for labeling products that do not have a marker groove

Commercial data

Item number	0825131
Packing unit	1 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	BG24
Product key	BG8113
Catalog page	Page 104 (C-5-2013)
GTIN	4046356355124
Weight per piece (including packing)	0.6 g
Weight per piece (excluding packing)	0.6 g
Customs tariff number	49119900
Country of origin	DE

SK 5,0 REEL P7,5 WH CUS - Marker card



0825131

<https://www.phoenixcontact.com/us/products/0825131>

Technical data

Product properties

Product type	Labeled terminal marker
Pitch	7.5 mm
Type	Label

Data management status

Article revision	02
------------------	----

Marking

Number of marker strips	10
-------------------------	----

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Foil strength	53 µm
Adhesive strength	20 µm
Adhesive	Acrylic
Color	white (RAL 9010)
Material	Polyester
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Ambient temperature (assembly)	> 15 °C
Recommended storage conditions	23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Dimensions

Height	5 mm
Pitch	7.5 mm

SK 5,0 REEL P7,5 WH CUS - Marker card



0825131

<https://www.phoenixcontact.com/us/products/0825131>

Standards and regulations


Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Notes

Order information:	Marking up to max. 25-pos.
--------------------	----------------------------

Drawings

Schematic diagram



- ① Horizontal
- ② Vertical

SK 5,0 REEL P7,5 WH CUS - Marker card



0825131

<https://www.phoenixcontact.com/us/products/0825131>

Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

SK 5,0 REEL P7,5 WH CUS - Marker card



0825131
<https://www.phoenixcontact.com/us/products/0825131>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com