

UC-TMF 5 PL-60 - Marker for terminal blocks



0828538

<https://www.phoenixcontact.com/us/products/0828538>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 5.2 mm, Number of individual labels: 96, text field height: 5.1 mm, text field width: 4.6 mm

Your advantages

- The markers, which are supplied in uniform sheets, can be printed onto quickly and easily using the BLUEMARK printing systems
- The UC-TM ... UniCard labeling range includes terminal markers for Phoenix Contact products with flat marker grooves
- The multi-section marking strips are easy to fit and can be easily separated if required
- The markers support multi-line labeling
- The sheets provide space for including function texts
- Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 0828538 |
| Packing unit | 60 pc |
| Minimum order quantity | 60 pc |
| Sales key | BG06 |
| Product key | BG2117 |
| GTIN | 4046356556088 |
| Weight per piece (including packing) | 8.515 g |
| Weight per piece (excluding packing) | 7 g |
| Customs tariff number | 39269097 |
| Country of origin | PL |

UC-TMF 5 PL-60 - Marker for terminal blocks



0828538

<https://www.phoenixcontact.com/us/products/0828538>

Technical data

Product properties

| | |
|--------------|------------------|
| Product type | Terminal marking |
| Pitch | 5.2 mm |
| Type | flat |

Data management status

| | |
|------------------|----|
| Article revision | 08 |
|------------------|----|

Marking

| | |
|-------------------------------------|-------------------|
| Number of individual labels | 96 |
| Number of individual labels per row | 12 |
| Identification technology | UV LED technology |

Dimensions

| | |
|-------------------|---------|
| Width | 5 mm |
| Text field width | 4.60 mm |
| Text field height | 5.10 mm |
| Pitch | 5.2 mm |

Material specifications

| | |
|--|--------------------------------|
| Color | white (RAL 9010) |
| Material | PA |
| Flammability rating according to UL 94 | V2 |
| Components | free from silicone and halogen |

Environmental and real-life conditions

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

Wipe resistance of inscriptions

| | |
|---------------|-------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
|---------------|-------------------------------------|

Ambient conditions

| | |
|---|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Mounting

| | |
|---------------|----------|
| Mounting type | latching |
|---------------|----------|

UC-TMF 5 PL-60 - Marker for terminal blocks



0828538

<https://www.phoenixcontact.com/us/products/0828538>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000761 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

UC-TMF 5 PL-60 - Marker for terminal blocks



0828538

<https://www.phoenixcontact.com/us/products/0828538>

Environmental product compliance

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com