

ZBF 13:UNBEDRUCKT - Zack Marker strip, flat



0829133

<https://www.phoenixcontact.com/sg/products/0829133>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 13 mm, lettering field size: 13 x 5.2 mm, Number of individual labels: 5

Your advantages

- Unlabeled marking strips can be custom-labeled with a plotter or by hand
- Other pitches available on request
- The ZBF zack marker strip system with flat marker groove is a marking solution for modular terminal blocks and electronics modules
- The multi-section marking strips are easy to fit and can be easily separated if required

Commercial data

Item number	0829133
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	*****
Product key	BG2112
Catalog page	Page 130 (C-3-2019)
GTIN	4046356546416
Weight per piece (including packing)	0.59 g
Weight per piece (excluding packing)	0.41 g
Customs tariff number	39269097
Country of origin	DE

ZBF 13:UNBEDRUCKT - Zack Marker strip, flat



0829133

<https://www.phoenixcontact.com/sg/products/0829133>

Technical data

Notes

General	Can be labeled with CMS
General	Can be labeled with CMS

Product properties

Product type	Terminal marking
Pitch	13 mm
Type	flat

Marking

Number of individual labels	5
Number of individual labels per row	5
Number of marker strips	10

Dimensions

Width	13 mm
Pitch	13 mm

Material specifications

Color	white
Material	PA
	PA
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

Environmental and real-life conditions

UV resistance

Specification	ISO 4892-2:2013-03 (following)
---------------	--------------------------------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Standards and regulations


Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
	DIN EN 61010-1 (VDE 0411-1)
	DIN VDE 0611
	DIN VDE 0611

Mounting

Mounting type	snapped
---------------	---------

Drawings

Schematic diagram



ZBF 13:UNBEDRUCKT - Zack Marker strip, flat



0829133

<https://www.phoenixcontact.com/sg/products/0829133>

Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunos Avenue 3, #04-00

Singapore 409836

+65 6228 4900

marketing@phoenixcontact.com.sg