

TMCP 1 M1 300 8,0A - Thermomagnetic device circuit breaker

0915823
<https://www.phoenixcontact.com/pc/products/0915823>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermal-magnetic circuit breaker, 1-pos., normal blow, 1 N/O contact and 1 N/C contact

Your advantages

- Individually adjustable with protective plugs
- Switch higher starting currents with the aid of the M1 characteristic curve
- High-level system transparency with integrated remote indication contact
- Fast, replacement part-free recommissioning after an event with the reconnection options

Commercial data

Item number	0915823
Packing unit	6 pc
Minimum order quantity	6 pc
Sales key	04
Product key	CLA123
Catalog page	Page 281 (CL-2002)
GTIN	4017918600662
Weight per piece (including packing)	47.16 g
Weight per piece (excluding packing)	47.16 g
Customs tariff number	85362010
Country of origin	DE

TMCP 1 M1 300 8,0A - Thermomagnetic device circuit breaker



0915823

<https://www.phoenixcontact.com/pc/products/0915823>

Technical data

Product properties

Product type	Thermomagnetic device circuit breakers
Product family	TMCP
Type	Male
Number of positions	1
No. of channels	1

Insulation characteristics

Overvoltage category	II
Degree of pollution	2

Electrical properties

Fuse type	Automatic device
-----------	------------------

General

Rated voltage	250 V AC
	65 V DC
Rated current I_N	8 A
Rated surge voltage	2.5 kV
Insulation resistance R_{ISO}	> 100 M Ω (500 V DC)
Auxiliary circuit	240 V AC / 1 A (Low-induction)
	65 V AC / 1 A (Low-induction)
Tripping method	TM (thermomagnetic)
Device resistance	0.02 Ω
Rated short-circuit switching capacity I_{cn}	800 A
	2500 A (32 V DC)
Short-circuit switching capacity	5000 A (UL 1077: 277 V AC)
	2000 A (UL 1077: 65 V DC)
Dielectric strength	3000 V AC (Actuation area)
	1500 V AC (Main to auxiliary circuit)
	1000 V AC (Auxiliary circuit 11 - 12 to 23 - 24)
Switching cycles, max.	10000 (At $1 \times I_N$, inductive)
Fuse	M1 (normal blow)
Contact switching type	1 N/O contact
	1 N/C contact

Connection data

Connection method	pluggable
Connection method	pluggable

Dimensions

TMCP 1 M1 300 8,0A - Thermomagnetic device circuit breaker



0915823

<https://www.phoenixcontact.com/pc/products/0915823>

Width	12.5 mm
Height	50 mm
Depth	78.5 mm
Complete module width	38 mm
Complete module height	115 mm
Complete module depth	121 mm

Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-2
Insulating material group	II
Insulating material	PA66

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30 (Actuation area)
	IP00 (Connection area)
Ambient temperature (operation)	-30 °C ... 60 °C
Humidity test	240 h, 95 % RH, 40 °C

Standards and regulations

Standards/specifications	EN 60934
Standards/specifications	UL 1077

Mounting

Mounting type	on base element
---------------	-----------------

TMCP 1 M1 300 8,0A - Thermomagnetic device circuit breaker



0915823

<https://www.phoenixcontact.com/pc/products/0915823>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/0915823>



CSA

Approval ID: 074317



UL Recognized

Approval ID: FILE E 140459



EAC

Approval ID: RU C-DE.A*30.B01546



VDE Zeichengenehmigung

Approval ID: 40029348

TMCP 1 M1 300 8,0A - Thermomagnetic device circuit breaker



0915823
<https://www.phoenixcontact.com/pc/products/0915823>

Classifications

ECLASS

ECLASS-11.0	27141116
ECLASS-12.0	27141116
ECLASS-13.0	27140401

ETIM

ETIM 9.0	EC003538
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

TMCP 1 M1 300 8,0A - Thermomagnetic device circuit breaker



0915823

<https://www.phoenixcontact.com/pc/products/0915823>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-25
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	64668a2e-9cf0-434e-addb-48c09c570958

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com