



100-C IEC Contactors

[100-C90KF400](#)



Representative Rendering, Not The Actual Product

100-C IEC Contactor, 230V 50/60Hz, Screw Terminals, Line Side, 85A, 4 N.O. 0 N.C. Main Contact Configuration, Single Pack

Product Details

CONTACTOR DATA	
Terminal Type	Screw Terminals
Rated Operating Current, AC-3	85A
Coil Voltage	230V 50/60Hz
No. of Poles	4 Poles
Coil Termination	Line Side
Contact Configuration	4 N.O. 0 N.C. Main Contact Configuration
Package Quantity	1
APPLICATION DATA	
Electrical Standards	UL
LOAD DATA [OPTIONAL]	
Utilization Category	AC-3 Squirrel-cage motor starting and stopping
Load FLA (Nameplate Value)	0 A
NEC FLA	0 A
Minimum Required FLA	0 A
LIFE DATA [OPTIONAL]	
Minimum Required Life	0 Mil. Oper.
Actual Life	Actual Life Cannot be Calculated (more information)...
TERMINAL MARKING POSITIONS USED	
100-C or 104-C Contactor	None
Front Mounted Auxiliary Contact	None
Left Side Auxiliary Contact	None
Right Side Auxiliary Contact	None
Interlock	None

Supporting Documentation and Downloads

- [Repair Parts List](#)
- [MCS 100-C Contactor Photo](#)

- [Short Circuit Ratings Data Sheet](#)
- [Technical Detail](#)