

Specifications



Photo is representative

Eaton 100668

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, black, lockable, max 60mm shaft, size 2

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element NA
CATALOG NUMBER	100668
MODEL CODE	NZM2-XTVDV-60-NA
EAN	4015081005680
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	190 mm
PRODUCT WIDTH	90 mm
PRODUCT WEIGHT	0.72 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	UL (File No. E140305) CSA-C22.2 No. 5-09 CSA (File No. 22086) UL (Category Control Number DIHS) CE marking UL listed CSA certified UL489 CSA (Class No. 1437-01) IEC60947
GLOBAL CATALOG	100668



Powering Business Worldwide

Product specifications

USED WITH	NZM2, N(S)2
FEATURES	Lockable Standard: black / gray
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGS	eaton-digital-nzm-catalog-ca013003en-en-us.pdf eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-008.eps eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-005.eps eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-004.eps
DRAWINGS	
INSTALLATION INSTRUCTIONS	eaton-door-coupling-rotary-handle-nzm1-2-xt-il01203005z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	DA-CS-nzm2_xtvd_60 DA-CD-nzm2_xtvd_60
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FITTED WITH:	Padlock
FRAME	NZM2
SUITABLE FOR	Power circuit breaker Switch disconnecter
COVER/DOOR TYPE	Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock not defeated in the locked OFF position. Door opens only with active rotation beyond the 0 position
LOCK NUMBER	Single lockable
LOCKING FACILITY	With door interlock Lockable on the handle on the switch using up to 3 padlocks
TYPE	Accessory Door coupling rotary handle
SPECIAL FEATURES	Complete including rotary drive and coupling parts Extension shaft

additionally required.
Cannot be combined with
mechanical interlock For
maximum shaft length 60
mm Without shaft support
Cannot be combined with
NZM...-XDZ additional
handle External warning
plate/designation label
can be clipped on. Door
coupling rotary handle for
operating the switch
through a closed control
panel door

DEGREE OF PROTECTION	IP66
/ NEMA ENCLOSURE TYPE	4X, 12

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

