

# Specifications



## Eaton 101041

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, MSC

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILA Accessory Auxiliary contact module
<b>CATALOG NUMBER</b>	101041
<b>MODEL CODE</b>	DILA-XHIT02
<b>EAN</b>	4015081009367
<b>PRODUCT LENGTH/DEPTH</b>	55 mm
<b>PRODUCT HEIGHT</b>	38 mm
<b>PRODUCT WIDTH</b>	36 mm
<b>PRODUCT WEIGHT</b>	0.039 kg
<b>CERTIFICATIONS</b>	VDE 0660 CSA CSA-C22.2 No. 14-05 UL 508 UL File No.: E29184 CSA Class No.: 3211-03 CSA File No.: 012528 UL Category Control No.: NKCR IEC/EN 60947 UL CE IEC/EN 60947-4-1
<b>GLOBAL CATALOG</b>	101041

## Product specifications

<b>TYPE</b>	Front mounting auxiliary contact, high version
<b>FEATURES</b>	Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to

## Resources

### CATALOGS

[Product Range Catalog Switching and protecting motors](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[DA-DC-00004777.pdf](#)

[DA-DC-00004783.pdf](#)

[DA-DC-00005005.pdf](#)

[DA-DC-00004972.pdf](#)

[DA-DC-00004819.pdf](#)

[DA-DC-00004988.pdf](#)

[DA-DC-00004983.pdf](#)

[DA-DC-00004784.pdf](#)

[DA-DC-00004976.pdf](#)

[DA-DC-00004792.pdf](#)

[DA-DC-00004810.pdf](#)

[DA-DC-00004815.pdf](#)

[DA-DC-00004811.pdf](#)

[DA-DC-00004816.pdf](#)

[DA-DC-00004789.pdf](#)

[DA-DC-00004880.pdf](#)

[DA-DC-00004996.pdf](#)

[DA-DC-00004881.pdf](#)

[DA-DC-00004992.pdf](#)

[DA-DC-00004937.pdf](#)

[DA-DC-00004913.pdf](#)

[DA-DC-00004912.pdf](#)

[DA-DC-00004776.pdf](#)

[DA-DC-00004246.pdf](#)

[eaton-contactors-module-dilm-dimensions-002.eps](#)

### DRAWINGS

[eaton-contactors-module-dila-accessory-3d-drawing.eps](#)

### ECAD MODEL

[ETN.101041.edz](#)

	be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>ELECTRIC CONNECTION TYPE</b>	Screw connection
<b>FITTED WITH:</b>	Switching elements according to EN 50005 Interlocked opposing contacts
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
<b>AMBIENT STORAGE</b>	80 °C

<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">WIN-WIN with push-in technology</a>
<b>MCAD MODEL</b>	<a href="#">DA-CD-dil_a_xhit</a> <a href="#">DA-CS-dil_a_xhit</a>
<b>SYSTEM OVERVIEW</b>	<a href="#">eaton-manual-motor-starters-assemblies-dila-accessory-explosion-drawing.eps</a>
<b>WIRING DIAGRAMS</b>	<a href="#">2100SWI-112</a>

<b>TEMPERATURE - MAX</b>	
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>CONVENTIONAL THERMAL CURRENT ITH AT 60°C (3-POLE, OPEN)</b>	16 A
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0.16 W
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
<b>NUMBER OF SWITCHES (FAULT SIGNAL)</b>	0
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V 6000 V AC
<b>SCREWDRIVER SIZE</b>	2, Terminal screw, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
<b>MOUNTING METHOD</b>	Front fastening
<b>CONNECTION</b>	Screw terminals
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONTROL CIRCUIT RELIABILITY</b>	$\lambda < 5 \times 1/10^7$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
<b>DEGREE OF PROTECTION</b>	IP20
<b>MODEL</b>	Top mounting
<b>LAMP HOLDER</b>	None
<b>FUNCTIONS</b>	For combination with electrical wiringlinks
<b>SAFE ISOLATION</b>	400 V AC, Between auxiliary contacts,

	According to EN 61140 400 V AC, Between coil and auxiliary contacts, According to EN 61140
<b>RATED OPERATIONAL CURRENT (IE)</b>	0.5 A at 110 V, DC L/R $\leq$ 50 ms (with 3 contacts in series) 6 A at 60 V, DC L/R $\leq$ 15 ms (with 1 contact in series) 10 A at 24 V, DC L/R $\leq$ 15 ms (with 1 contact in series) 1 A at 60 V, DC L/R $\leq$ 50 ms (with 3 contacts in series) 3 A at 110 V, DC L/R $\leq$ 15 ms (with 1 contact in series) 0.25 A at 220 V, DC L/R $\leq$ 50 ms (with 3 contacts in series) 2.5 A at 24 V, DC L/R $\leq$ 50 ms (with 3 contacts in series) 1 A at 220 V, DC L/R $\leq$ 15 ms (with 1 contact in series)
<b>LIFESPAN, ELECTRICAL</b>	1,300,000 Operations (at 230 V, AC-15, 3 A)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
<b>STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS</b>	0 W
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
<b>NUMBER OF POLES</b>	Two-pole
<b>SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING</b>	10 A gG/gL, 500 V, Max. Fuse, Contacts
<b>SHORT-CIRCUIT PROTECTION RATING</b>	Max. 10 A gG/gL, Fuse, Without welding, Auxiliary contacts
<b>RATED INSULATION VOLTAGE (UI)</b>	690 V

<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>	4 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>	4 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V</b>	1.5 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V</b>	0.5 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V</b>	0.25 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V</b>	2.5 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V</b>	1 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	4 A
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	500 V
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	2 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals 1 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals 2 x (0.75 - 2.5) mm <sup>2</sup> , Screw terminals
<b>TIGHTENING TORQUE</b>	1.2 Nm, Screw terminals
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	18 - 14, Screw terminals
<b>SHOCK RESISTANCE</b>	5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

