

Specifications

Eaton 101340

Eaton Moeller series xPole - PLI MCB. PLI, 3-pole+N, tripping characteristic: C, rated current In: 10 A, rated switching capacity IEC/EN 60898-1: 10 kA

General specifications

PRODUCT NAME	Eaton Moeller series xPole - PLI MCB
CATALOG NUMBER	101340
EAN	4015081012756
PRODUCT LENGTH/DEPTH	84 mm
PRODUCT HEIGHT	75.5 mm
PRODUCT WIDTH	70 mm
PRODUCT WEIGHT	0.391 kg
COMPLIANCES	RoHS conform
MODEL CODE	PLI-C10/3N



Powering Business Worldwide

Delivery program

APPLICATION

- Switchgear for residential and commercial applications
- xPole - Switchgear for residential and commercial applications

NUMBER OF POLES	Three-pole + N
-----------------	----------------

NUMBER OF POLES (TOTAL)	4
-------------------------	---

NUMBER OF POLES (PROTECTED)	3
-----------------------------	---

TRIPPING CHARACTERISTIC	C
-------------------------	---

RELEASE CHARACTERISTIC	C
------------------------	---

AMPERAGE RATING	10 A
-----------------	------

TYPE

- Miniature circuit breaker
- PLI

Technical data - electrical

VOLTAGE TYPE	AC
--------------	----

RATED OPERATIONAL VOLTAGE (UE) - MAX	400 V
--------------------------------------	-------

RATED INSULATION VOLTAGE (UI)	440 V
-------------------------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
--	------

FREQUENCY RATING - MIN	50 Hz
------------------------	-------

FREQUENCY RATING - MAX	60 Hz
------------------------	-------

RATED SWITCHING CAPACITY (IEC/EN 60898-1)	10 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V	10 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V	10 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V	0 kA
--	------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V	0 kA
--	------

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	2
------------------	---

Technical data - mechanical

**WIDTH IN NUMBER OF
MODULAR SPACINGS** 4

BUILT-IN DEPTH 70.5 mm

DEGREE OF PROTECTION IP20

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MIN** 1 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MAX** 25 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MIN** 1 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MAX** 25 mm²

Additional information

**CURRENT LIMITING
CLASS** 3

FEATURES Additional equipment
possible
Concurrently switching N-
neutral

SPECIAL FEATURES Ambient temperature hint:
a 1 °C increase results in a
0.5% linear reduction of
current carrying capacity

USED WITH PLI
Miniature circuit breaker

Design verification as per IEC/EN 61439 - technical data

**RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN)** 10 A

**HEAT DISSIPATION PER
POLE, CURRENT-
DEPENDENT** 0 W

**EQUIPMENT HEAT
DISSIPATION, CURRENT-
DEPENDENT** 4.7 W

**STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT** 0 W

**HEAT DISSIPATION
CAPACITY** 0 W

**AMBIENT OPERATING
TEMPERATURE - MIN** -25 °C

**AMBIENT OPERATING
TEMPERATURE - MAX** 75 °C

Resources

[eaton-xpole-protective-
devices-catalog-
ca019014en-en-us.pdf](#)

CATALOGUES [eaton-xpole-accessories-
ca019015en-en-us.pdf](#)

[eaton-xpole-pli-mcb-
catalog-ca019072en-en-
us.pdf](#)

**DECLARATIONS OF
CONFORMITY** [DA-DC-03_PLI](#)

DRAWINGS [eaton-xpole-pli-mcb-
dimensions.jpg](#)

**INSTALLATION
INSTRUCTIONS** [IL019073ZU](#)

[eaton-pli mcb 4p-
drawing.dwg](#)

MCAD MODEL [eaton-pli mcb 4p-3d-
model.stp](#)

PEP ECO-PASSPORT [EATO-00048-V01.01-EN](#)

WIRING DIAGRAMS [eaton-xpole-mmc4-6-m-
mcb-wiring-diagram-
004.jpg](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

