## Specifications

## Eaton 101487

Eaton Moeller® series DILM Secondary terminal wire kit, star-delta, DILM115-150

General specificatio	ns
PRODUCT NAME	Eaton Moeller® series DILM wiring kit
CATALOG NUMBER	101487
MODEL CODE	DILM150-XSL
EAN	4015081014071
PRODUCT LENGTH/DEPTH	175 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	120 mm
PRODUCT WEIGHT	1.09 kg
CERTIFICATIONS	CE CSA-C22.2 No. 14-05 UL File No.: E36332 UL UL Category Control No.: NLRV CSA Class No.: 2411-03, 3211-04 CSA IEC/EN 60947-4-1 CSA File No.: 012528 UL 508
GLOBAL CATALOG	101487



Product specification	C
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.

Resources	
CATALOGS	SmartWire-DT Catalog
	Product Range Catalog Switching and protecting motors
	eaton-product-overview-
	for-machinery-catalogue- ca08103003zen-en-us.pdf
DRAWINGS	eaton-contactors-star- delta-dilm-wiring-kit-3d- drawing.eps
ECAD MODEL	ETN.101487.edz
INSTALLATION INSTRUCTIONS	<u>IL03407045Z</u>
MCAD MODEL	dilm150_xsl.dwg
	dilm150 xsl.stp

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
FITTED WITH:	Star-point bridge
ACCESSORY/SPARE PART TYPE	Connecting bridge
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	17.1 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	5.7 W
FUNCTIONS	Main current wiring for star-delta combination
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	225 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
PRODUCT CATEGORY	Accessories

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



## **Eaton Corporation plc**

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









