


# SACC-DSI-FS-5CON-M16/0,5-18AWG - Device connector rear mounting



1020176

<https://www.phoenixcontact.com/pc/products/1020176>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Socket, straight, M12, coding: A, on free cable end, Rear wall/screw mounting, M16 x 1.5, Individual wires, cable length: 0.5 m, 0.75 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1238073

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1020176                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 100 pc                         |
| Note                                 | Made to order (non-returnable) |
| Product key                          | ABQCHB                         |
| GTIN                                 | 4055626516264                  |
| Weight per piece (including packing) | 55 g                           |
| Weight per piece (excluding packing) | 22.22 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | DE                             |

# SACC-DSI-FS-5CON-M16/0,5-18AWG - Device connector rear mounting



1020176

<https://www.phoenixcontact.com/pc/products/1020176>

## Technical data

### Notes

| Order information: | Lock nut is included in the scope of delivery  |
|--------------------|--|
| <b>Safety note</b> |  |
| Safety note        | <p><b>WARNING:</b> The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none"><li>• <b>WARNING:</b> Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li><li>• <b>WARNING:</b> Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.</li><li>• The products are suitable for applications in plant, controller, and electrical device engineering.</li><li>• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.</li><li>• Assembled products may not be manipulated or improperly opened.</li><li>• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a>).</li><li>• When using the product in direct connection with third-party manufacturers, the user is responsible.</li><li>• For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li><li>• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.</li><li>• Observe the corresponding technical data. You will find information:<ul style="list-style-type: none"><li>o On the product</li><li>o On the packing label</li><li>o In the supplied documentation</li><li>o Online at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a> under the product</li></ul></li><li>• Only use tools recommended by Phoenix Contact</li><li>• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a></li><li>• Ensure that the protective or functional ground has been properly connected.</li><li>• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector</li></ul> |

# SACC-DSI-FS-5CON-M16/0,5-18AWG - Device connector rear mounting



1020176

<https://www.phoenixcontact.com/pc/products/1020176>

- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

## Mounting

|               |                                    |
|---------------|------------------------------------|
| Mounting type | Rear wall/screw mounting M16 x 1.5 |
|---------------|------------------------------------|

## Product properties

|                      |                                   |
|----------------------|-----------------------------------|
| Product type         | Circular connectors (device side) |
| Number of positions  | 5                                 |
| No. of cable outlets | 1                                 |
| Coding               | A                                 |
| Thread type          | M12                               |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

## Electrical properties

|                       |           |
|-----------------------|-----------|
| Rated surge voltage   | 1.5 kV AC |
| Nominal voltage $U_N$ | 60 V      |
| Nominal current $I_N$ | 4 A       |

## Connection data

|                         |                      |
|-------------------------|----------------------|
| Conductor connection    |                      |
| Connection method       | Individual wires     |
| Contact connection type | Socket               |
| Conductor cross section | 0.75 mm <sup>2</sup> |

## Mechanical properties

|                             |       |
|-----------------------------|-------|
| Mechanical data             |       |
| Insertion/withdrawal cycles | > 100 |

## Connector

|                   |          |
|-------------------|----------|
| Connection 1      |          |
| Head design       | Socket   |
| Head cable outlet | straight |
| Head thread type  | M12      |
| Coding            | A        |

|              |                |
|--------------|----------------|
| Connection 2 |                |
| Head design  | free cable end |

# SACC-DSI-FS-5CON-M16/0,5-18AWG - Device connector rear mounting



1020176

<https://www.phoenixcontact.com/pc/products/1020176>

## Cable/line

|                     |                      |
|---------------------|----------------------|
| Cable length        | 0.5 m                |
| Cable cross section | 0.75 mm <sup>2</sup> |

## Environmental and real-life conditions

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Degree of protection            | IP67 (When plugged in)<br>IP65 (When plugged in)<br>IP65/IP67 |
| Ambient temperature (operation) | -25 °C ... 85 °C  |

## Standards and regulations

|                          |                              |
|--------------------------|------------------------------|
| Standards/specifications | according to IEC 61076-2-101 |
|--------------------------|------------------------------|

# SACC-DSI-FS-5CON-M16/0,5-18AWG - Device connector rear mounting



1020176

<https://www.phoenixcontact.com/pc/products/1020176>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SACC-DSI-FS-5CON-M16/0,5-18AWG - Device connector rear mounting



1020176

<https://www.phoenixcontact.com/pc/products/1020176>

## Environmental product compliance

### EU RoHS

|  |      |
|--|------|
| Fulfils EU RoHS substance requirements | Yes  |
| Exemption                              | 6(c) |

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-50<br><br>An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
|--|--|

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | c37f07c7-124a-45d2-9fda-72b405a282d9 |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarkstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
info@phoenixcontact.com