

# Specifications



Photo is representative



## Eaton 102182

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: D, rated current In: 4 A, Switchgear for export to North America (UL-listed)

### General specifications

|                             |                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB                                                                                                                                                                                                                                                                                                        |
| <b>CATALOG NUMBER</b>       | 102182                                                                                                                                                                                                                                                                                                                                                   |
| <b>MODEL CODE</b>           | FAZ-D4/2-NA                                                                                                                                                                                                                                                                                                                                              |
| <b>EAN</b>                  | 4015081020584                                                                                                                                                                                                                                                                                                                                            |
| <b>PRODUCT LENGTH/DEPTH</b> | 105 mm                                                                                                                                                                                                                                                                                                                                                   |
| <b>PRODUCT HEIGHT</b>       | 75.5 mm                                                                                                                                                                                                                                                                                                                                                  |
| <b>PRODUCT WIDTH</b>        | 35.4 mm                                                                                                                                                                                                                                                                                                                                                  |
| <b>PRODUCT WEIGHT</b>       | 0.246 kg                                                                                                                                                                                                                                                                                                                                                 |
| <b>COMPLIANCES</b>          | RoHS conform                                                                                                                                                                                                                                                                                                                                             |
| <b>CERTIFICATIONS</b>       | CE marking<br>UL 489<br>CSA (File No. 204453)<br>CSA (Class No. 1432-01)<br>UL (File No. E235139)<br>North America (UL listed, CSA certified)<br>CSA-C22.2 No. 5-09<br>Specially designed for North America, suitable as BCPD<br>IEC/EN 60947-2<br>UL 489, CSA C22.2 No. 5<br>IEC 60947-2<br>UL (Category Control Number DIVQ)<br>EN45545-2<br>IEC 61373 |

## Delivery program

### APPLICATION

- Feeder circuits, branch circuits
- Switchgear for export to North America (UL-listed)

**NUMBER OF POLES** Two-pole

**NUMBER OF POLES (TOTAL)** 2

**NUMBER OF POLES (PROTECTED)** 2

**TRIPPING CHARACTERISTIC** D

**RELEASE CHARACTERISTIC** D

**AMPERAGE RATING** 4 A

### TYPE

- FAZ-NA
- Miniature circuit breaker

## Technical data - electrical

**VOLTAGE TYPE** AC

**VOLTAGE RATING** 277 V AC / 480 V AC

**VOLTAGE RATING AT DC** 60 V DC

**VOLTAGE RATING (IEC/EN 60947-2)** 415 V

**VOLTAGE RATING (UL)** 480Y/277 V

**RATED OPERATIONAL VOLTAGE (UE) - MAX** 415 V

**RATED INSULATION VOLTAGE (UI)** 440 V

**RATED IMPULSE WITHSTAND VOLTAGE (UIMP)** 4 kV

**FREQUENCY RATING - MIN** 50 Hz

**FREQUENCY RATING - MAX** 60 Hz

**RATED SWITCHING CAPACITY (IEC/EN 60947-2)** 15 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V** 0 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V** 0 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V** 15 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V** 15 kA

**SELECTIVITY CLASS** 3

**OVERVOLTAGE CATEGORY** III

**POLLUTION DEGREE** 2

**LIFESPAN, ELECTRICAL** 20000 operations

**DIRECTION OF INCOMING SUPPLY** As required

## Technical data - mechanical

|                                                                |                                                                                                                                       |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <b>FRAME</b>                                                   | 45 mm                                                                                                                                 |
| <b>ENCLOSURE WIDTH</b>                                         | 105 mm                                                                                                                                |
| <b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>                     | 2                                                                                                                                     |
| <b>BUILT-IN DEPTH</b>                                          | 70.5 mm                                                                                                                               |
| <b>MOUNTING WIDTH PER POLE</b>                                 | 17.7 mm                                                                                                                               |
| <b>MOUNTING WIDTH</b>                                          | 17.7 mm                                                                                                                               |
| <b>MOUNTING METHOD</b>                                         | Top-hat rail IEC/EN 60715                                                                                                             |
| <b>MOUNTING POSITION</b>                                       | As required                                                                                                                           |
| <b>DEGREE OF PROTECTION</b>                                    | UL/CSA Type: -<br>IP20 (IEC)<br>IP20<br>IP40 (when fitted)                                                                            |
| <b>TERMINALS (TOP AND BOTTOM)</b>                              | Twin-purpose terminals                                                                                                                |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>  | 1 mm <sup>2</sup>                                                                                                                     |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>  | 25 mm <sup>2</sup>                                                                                                                    |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b> | 1 mm <sup>2</sup>                                                                                                                     |
| <b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b> | 25 mm <sup>2</sup>                                                                                                                    |
| <b>TERMINAL PROTECTION</b>                                     | Finger and hand touch safe, DGUV VS3, EN 50274                                                                                        |
| <b>TIGHTENING TORQUE</b>                                       | UL: 2.8 Nm (25 lb-in) for AWG 10 - AWG 8<br>UL: 4 Nm (36 lb-in) for AWG 6<br>Max. 2.4 Nm<br>UL: 2.4 Nm (21 lb-in) for AWG 18 - AWG 12 |

## Design verification as per IEC/EN - technical data

|                                                                      |        |
|----------------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 4 A    |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>                  | 0 W    |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>                 | 2.9 W  |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>                | 0 W    |
| <b>HEAT DISSIPATION CAPACITY</b>                                     | 0 W    |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                           | -25 °C |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                           | 75 °C  |

## Design verification as per IEC/EN 61439

|                                                                                         |                                                                    |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                         |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                         |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                         |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                         |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                         |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                         |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                                          | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                                           | Meets the product standard's requirements.                         |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                                           | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>                           | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>                                | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                                         | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                                         | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                                                 | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>                                             | Is the panel builder's responsibility.                             |

## Additional information

|                               |                                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>CURRENT LIMITING CLASS</b> | 3                                                                                                         |
| <b>FEATURES</b>               | Additional equipment possible                                                                             |
| <b>FUNCTIONS</b>              | Current limiting circuit breaker                                                                          |
| <b>SPECIAL FEATURES</b>       | Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity |
| <b>USED WITH</b>              | FAZ-NA<br>Miniature circuit breaker                                                                       |

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

## Resources

**BROCHURES** [eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf](#)

**CATALOGUES** [eaton-xeffect-faz-na-rt-mcb-catalog-ca003032en-en-us.pdf](#)

[eaton-xeffect-faz-na,-mcb-3d-drawing-010.jpg](#)

[eaton-xeffect-faz-na,-mcb-3d-drawing-009.jpg](#)

[eaton-mcb-xeffect-faz-na,-characteristic-curve-004.eps](#)

**CHARACTERISTIC CURVE** [eaton-xeffect-faz-na,-mcb-dimensions-005.jpg](#)

[eaton-xeffect-faz-na,-mcb-characteristic-curve-002.jpg](#)

[eaton-xeffect-faz-na,-mcb-characteristic-curve.jpg](#)

[eaton-mcb-xeffect-faz-na,-characteristic-curve-003.eps](#)

**DECLARATIONS OF CONFORMITY** [03\\_faz-du\\_111017.pdf](#)  
[DA-DC-03 FAZ-B-C-D](#)  
[DA-DC-03 FAZ-NA](#)  
[DA-DC-03 FAZ-DU](#)

**DRAWINGS** [eaton-xeffect-faz-na,-mcb-dimensions.jpg](#)  
[eaton-mcb-xeffect-faz-na,-3d-drawing-003.eps](#)

**ECAD MODEL** [ETN.FAZ-D4\\_2-NA](#)

**INSTALLATION INSTRUCTIONS** [IL019133ZU](#)

**MCAD MODEL** [faz\\_na\\_2p.dwg](#)  
[faz\\_na\\_2p.stp](#)

**WIRING DIAGRAMS** [eaton-mcb-xeffect-faz-na,-wiring-diagram-003.eps](#)  
[eaton-xpole-mmc4-6-m-mcb-wiring-diagram-003.jpg](#)

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

