

# Specifications



Photo is representative



## Eaton 102256

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 3-pole, tripping characteristic: C, rated current In: 40 A, Switchgear for export to North America (UL-listed)

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB
<b>CATALOG NUMBER</b>	102256
<b>MODEL CODE</b>	FAZ-C40/3-NA
<b>EAN</b>	4015081021321
<b>PRODUCT LENGTH/DEPTH</b>	105 mm
<b>PRODUCT HEIGHT</b>	75.5 mm
<b>PRODUCT WIDTH</b>	53.1 mm
<b>PRODUCT WEIGHT</b>	0.382 kg
<b>COMPLIANCES</b>	RoHS conform
<b>CERTIFICATIONS</b>	IEC/EN 60947-2 UL 489, CSA C22.2 No. 5 CE marking CSA (File No. 204453) IEC 60947-2 UL (File No. E235139) Specially designed for North America, suitable as BCPD CSA-C22.2 No. 5-09 CSA (Class No. 1432-01) UL (Category Control Number DIVQ) UL 489 North America (UL listed, CSA certified) EN45545-2 IEC 61373

## Delivery program

### APPLICATION

- Feeder circuits, branch circuits
- Switchgear for export to North America (UL-listed)

**NUMBER OF POLES** Three-pole

**NUMBER OF POLES (TOTAL)** 3

**NUMBER OF POLES (PROTECTED)** 3

**TRIPPING CHARACTERISTIC** C

**RELEASE CHARACTERISTIC** C

**AMPERAGE RATING** 40 A

### TYPE

- FAZ-NA
- Miniature circuit breaker

## Technical data - electrical

**VOLTAGE TYPE** AC

**VOLTAGE RATING** 240 V AC

**VOLTAGE RATING AT DC** 60 V DC

**VOLTAGE RATING (IEC/EN 60947-2)** 440 V

**VOLTAGE RATING (UL)** 240 V

**RATED OPERATIONAL VOLTAGE (UE) - MAX** 415 V

**RATED INSULATION VOLTAGE (UI)** 440 V

**RATED IMPULSE WITHSTAND VOLTAGE (UIMP)** 4 kV

**FREQUENCY RATING - MIN** 50 Hz

**FREQUENCY RATING - MAX** 60 Hz

**RATED SWITCHING CAPACITY (IEC/EN 60947-2)** 15 kA

**BREAKING CAPACITY** 10 kA (UL489)

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V** 0 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V** 0 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V** 15 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V** 15 kA

**SELECTIVITY CLASS** 3

**OVERVOLTAGE CATEGORY** III

**POLLUTION DEGREE** 2

**LIFESPAN, ELECTRICAL** 20000 operations

**DIRECTION OF INCOMING SUPPLY** As required

## Technical data - mechanical

<b>FRAME</b>	45 mm
<b>ENCLOSURE WIDTH</b>	105 mm
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	3
<b>BUILT-IN DEPTH</b>	70.5 mm
<b>MOUNTING WIDTH PER POLE</b>	17.7 mm
<b>MOUNTING WIDTH</b>	17.7 mm
<b>MOUNTING METHOD</b>	Top-hat rail IEC/EN 60715
<b>MOUNTING POSITION</b>	As required
<b>DEGREE OF PROTECTION</b>	UL/CSA Type: - IP40 (when fitted) IP20 (IEC) IP20
<b>TERMINALS (TOP AND BOTTOM)</b>	Twin-purpose terminals
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
<b>TERMINAL PROTECTION</b>	Finger and hand touch safe, DGUV VS3, EN 50274
<b>TIGHTENING TORQUE</b>	Max. 2.4 Nm UL: 2.4 Nm (21 lb-in) for AWG 18 - AWG 12 UL: 4 Nm (36 lb-in) for AWG 6 UL: 2.8 Nm (25 lb-in) for AWG 10 - AWG 8

## Design verification as per IEC/EN - technical data

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	40 A
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	12.1 W
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>	0 W
<b>HEAT DISSIPATION CAPACITY</b>	0 W
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	75 °C

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>	Is the panel builder's responsibility.

## Additional information

<b>CURRENT LIMITING CLASS</b>	3
<b>FEATURES</b>	Additional equipment possible
<b>FUNCTIONS</b>	Current limiting circuit breaker
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>USED WITH</b>	FAZ-NA Miniature circuit breaker

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

## Resources

**BROCHURES** [eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf](#)

**CATALOGUES** [eaton-xeffect-faz-na-rt-mcb-catalog-ca003032en-en-us.pdf](#)

[eaton-xeffect-faz-na,-mcb-dimensions-003.jpg](#)

[eaton-mcb-xeffect-faz-na,-characteristic-curve.eps](#)

[eaton-xeffect-faz-na,-mcb-characteristic-curve.jpg](#)

**CHARACTERISTIC CURVE** [eaton-xeffect-faz-na,-mcb-3d-drawing-003.jpg](#)

[eaton-mcb-xeffect-faz-na,-characteristic-curve-002.eps](#)

[eaton-xeffect-faz-na,-mcb-3d-drawing-007.jpg](#)

[eaton-xeffect-faz-na,-mcb-characteristic-curve-002.jpg](#)

**DECLARATIONS OF CONFORMITY** [DA-DC-03 FAZ-NA](#)  
[DA-DC-03 FAZ-B-C-D](#)

**DRAWINGS** [eaton-xeffect-faz-na,-mcb-dimensions.jpg](#)

[eaton-mcb-xeffect-faz-na,-3d-drawing-002.eps](#)

**ECAD MODEL** [ETN.FAZ-C40\\_3-NA](#)

**INSTALLATION INSTRUCTIONS** [IL019133ZU](#)

**MCAD MODEL** [eaton-non-selective-universal-mcb-drawings-faz-na-3p.dwg](#)  
[eaton-non-selective-universal-mcb-3d-models-faz-na-3p.stp](#)

[eaton-mcb-xeffect-faz-na,-wiring-diagram-002.eps](#)

**WIRING DIAGRAMS** [eaton-xpole-mmc4-6-m-mcb-wiring-diagram-005.jpg](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

