

# Specifications



Photo is representative

## Eaton 103033

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 33A, N1-S33-CNA

### General specifications

|                             |   |
|-----------------------------|---|
| <b>PRODUCT NAME</b>         | Eaton Moeller series NZM - Molded case circuit breaker  |
| <b>CATALOG NUMBER</b>       | 103033  |
| <b>MODEL CODE</b>           | NZMN1-S33-CNA   |
| <b>EAN</b>                  | 4015081028726   |
| <b>PRODUCT LENGTH/DEPTH</b> | 88 mm   |
| <b>PRODUCT HEIGHT</b>       | 165.5 mm  |
| <b>PRODUCT WIDTH</b>        | 90 mm   |
| <b>PRODUCT WEIGHT</b>       | 1.046 kg  |
| <b>COMPLIANCES</b>          | RoHS conform  |
| <b>CERTIFICATIONS</b>       | UL/CSA<br>CSA (Class No. 1432-01)<br>UL 489<br>CSA (File No. 22086)<br>UL (Category Control Number DKPU2)<br>Specially designed for North America<br>CSA-C22.2 No. 5-09<br>CSA certified<br>UL (File No. E31593)<br>UL listed |
| <b>GLOBAL CATALOG</b>       | 103033  |

## Product specifications

|   |  |
|---|--|
| <b>AMPERAGE RATING</b>  | 33 A   |
| <b>VOLTAGE RATING</b>   | 690 V - 690 V  |
| <b>10.10 TEMPERATURE RISE</b>   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.   |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.   |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.   |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.   |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.   |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.6 MECHANICAL IMPACT</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.7 INSCRIPTIONS</b>  | Meets the product standard's requirements.   |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>  | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.4 CLEARANCES AND</b>  | Meets the product  |

## Resources

|                                   |  |
|-----------------------------------|--|
| <b>BROCHURES</b>                  | <a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a>  |
| <b>CATALOGS</b>                   | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a>   |
| <b>CHARACTERISTIC CURVE</b>       | <a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve.eps</a><br><a href="#">eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-002.eps</a>   |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-058.eps</a><br><a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250289en.pdf</a>  |
| <b>DRAWINGS</b>                   | <a href="#">eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps</a><br><a href="#">eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps</a><br><a href="#">eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-006.eps</a> |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">eaton-circuit-breaker-switch-disconnector-nzmb-il01203004z.pdf</a><br><a href="#">Introduction of the new digital circuit breaker NZM</a>  |
| <b>INSTALLATION VIDEOS</b>        | <a href="#">The new digital NZM Range</a>  |
| <b>MCAD MODEL</b>                 | <a href="#">DA-CS-nzm1_3p</a><br><a href="#">eaton-molded-case-switches-mcad-3d-models-nzm1-3p-na-cna.stp</a><br><a href="#">DA-CD-nzm1_3p</a>   |
| <b>TECHNICAL DATA SHEETS</b>      | <a href="#">eaton-molded-case-switches-mcad-drawings-nzm1-3p-na-cna.dwg</a><br><a href="#">eaton-nzm-technical-information-sheet</a>   |

|   |  |
|---|--|
| <b>CREEPAGE DISTANCES</b>                                       | standard's requirements.   |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.   |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.   |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.   |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.   |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.   |
| <b>POLLUTION DEGREE</b>   | 3  |
| <b>MOUNTING METHOD</b>  | Built-in device fixed built-in technique<br>Fixed  |
| <b>CLIMATIC PROOFING</b>  | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                       |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>            | 3.43 W   |
| <b>ISOLATION</b>  | 500 V AC (between auxiliary contacts and main contacts)<br>300 V AC (between the auxiliary contacts) |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                      | 70 °C  |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                      | -25 °C   |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                        | 70 °C  |
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                        | 40 °C  |
| <b>PROTECTION AGAINST DIRECT CONTACT</b>                        | Finger and back-of-hand proof to VDE 0106 part 100   |
| <b>RATED INSULATION VOLTAGE (UI)</b>                            | 690 V  |
| <b>RATED OPERATING POWER AT AC-3, 230 V</b>                     | 7.5 kW   |

|   |   |
|---|---|
| <b>RATED OPERATING POWER AT AC-3, 400 V</b>       | 15 kW   |
| <b>SWITCH OFF TECHNIQUE</b>                       | Magnetic  |
| <b>DEGREE OF PROTECTION</b>                       | IP20<br>IP20 (basic degree of protection, in the operating controls area)   |
| <b>DIRECTION OF INCOMING SUPPLY</b>               | As required   |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b> | Other   |
| <b>LIFESPAN, MECHANICAL</b>                       | 20000 operations  |
| <b>OVERVOLTAGE CATEGORY</b>                       | III   |
| <b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>      | IP66 (with door coupling rotary handle)<br>IP40 (with insulating surround)  |
| <b>DEGREE OF PROTECTION (TERMINATIONS)</b>        | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)  |
| <b>NUMBER OF POLES</b>                            | Three-pole  |
| <b>TERMINAL CAPACITY (COPPER STRIP)</b>           | Max. 9 segments of 9 mm x 0.8 mm at box terminal<br>Min. 2 segments of 9 mm x 0.8 mm at box terminal  |
| <b>LIFESPAN, ELECTRICAL</b>                       | 7500 operations at 400 V AC-3<br>7500 operations at 415 V AC-3<br>5000 operations at 690 V AC-3   |
| <b>FUNCTIONS</b>                                  | Short-circuit protection  |
| <b>TYPE</b>                                       | Circuit breaker   |
| <b>SPECIAL FEATURES</b>                           | <ul style="list-style-type: none"> <li>Rated current = rated uninterrupted current: 33 A</li> <li>This circuit-breaker is only allowed to be used for UL/CSA applications.</li> <li>Motor protection in conjunction with contactor and overload relay</li> <li>With short-circuit release</li> <li>Without overload release <math>I_r</math></li> </ul> |

|  |  |
|--|--|
| <b>APPLICATION</b>   | Branch circuits, feeder circuits   |
| <b>SHOCK RESISTANCE</b>  | 20 g (half-sinusoidal shock 20 ms)   |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>                   | 33 A   |
| <b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX</b>                                 | 462 A  |
| <b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN</b>                                 | 264 A  |
| <b>HANDLE TYPE</b>   | Rocker lever   |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MAX</b>  | 462 A  |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>  | 264 A  |
| <b>NUMBER OF OPERATIONS PER HOUR - MAX</b>   | 120  |
| <b>OVERLOAD CURRENT SETTING (IR) - MAX</b>   | 0 A  |
| <b>OVERLOAD CURRENT SETTING (IR) - MIN</b>   | 0 A  |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ</b> | 50 kA  |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ</b>     | 50 kA  |
| <b>STANDARD TERMINALS</b>  | Box terminal   |
| <b>RATED OPERATING VOLTAGE UE (UL) - MAX</b>   | 480 Y / 277 V  |
| <b>RELEASE SYSTEM</b>  | Thermomagnetic release   |
| <b>SHORT-CIRCUIT TOTAL BREAKTIME</b>   | < 10 ms  |
| <b>TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)</b>                              | 16 mm <sup>2</sup> (1x) at tunnel terminal   |
| <b>TERMINAL CAPACITY (CONTROL CABLE)</b>   | 16 mm <sup>2</sup> - 18 mm <sup>2</sup> (2x)<br>14 mm <sup>2</sup> - 18 mm <sup>2</sup> (1x)                       |
| <b>TERMINAL CAPACITY (COPPER BUSBAR)</b>   | Min. 12 mm x 5 mm direct at switch rear-side connection<br>Max. 16 mm x 5 mm direct at switch rear-side connection |

|  |   |
|--|---|
|  | M6 at rear-side screw connection  |
| <b>TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)</b>                                | 6 mm <sup>2</sup> - 9 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>6 mm <sup>2</sup> (1x) at tunnel terminal<br>6 mm <sup>2</sup> - 12 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>6 mm <sup>2</sup> - 12 mm <sup>2</sup> (1x) at box terminal |
| <b>TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)</b>                             | 4 mm <sup>2</sup> - 3/0 mm <sup>2</sup> (1x) at tunnel terminal<br>4 mm <sup>2</sup> - 2/0 mm <sup>2</sup> (1x) at box terminal<br>4 mm <sup>2</sup> - 2/0 mm <sup>2</sup> (1x) direct at switch rear-side connection   |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (IEC/EN 60947) AT 400/415 V, 50/60 Hz</b> | 50 kA   |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS</b>                    | 6000 V  |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS</b>                         | 6000 V  |
| <b>POWER LOSS</b>  | 3.4 W   |

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

