



104-C Reversing Contactors

[104-C09EJ22](#)



Representative Rendering, Not The Actual Product

104-C Reversing Contactors, 9A, Line Side, 24V DC (w/Elec. Coil), 1 N.O. 1 N.C.

Product Details

ASSEMBLY	
Factory or User Assembled?	Factory Assembled
CONTACTOR DATA	
Terminal Type	Screw Terminals
Rated Operating Current, AC-3	9A
Coil Voltage	24V DC Electronic Coil
Coil Termination	Line Side
Auxiliary Contact Configuration	1 N.O. 1 N.C.
APPLICATION DATA	
Electrical Standards	UL
LOAD DATA [OPTIONAL]	
Utilization Category	AC-3 Squirrel-cage motor starting and stopping
Load FLA (Nameplate Value)	0 A
NEC FLA	0 A
Minimum Required FLA	0 A
LIFE DATA [OPTIONAL]	
Minimum Required Life	0 Mil. Oper.
Actual Life	Actual Life Cannot be Calculated (more information)...
ADDITIONAL INFORMATION	
Notice	See Pub. 0100C-1.0.1 for additional electrical life information.
TERMINAL MARKING POSITIONS USED	
100-C or 104-C Contactor	1_
Front Mounted Auxiliary Contact	None
Front Mounted Auxiliary Contact (Right Side if 104C)	None
Left Side Auxiliary Contact	None
Right Side Auxiliary Contact	None
Interlock	2_

Supporting Documentation and Downloads

- [Photo](#)
- [Technical Detail](#)