Specifications



Photo is representative

Eaton 104643

Eaton Moeller series NZM - Molded Case Circuit Breaker. Terminal cover, knockout, 4p, NZM3

| General specifications | | |
|-------------------------|--|--|
| PRODUCT NAME | Eaton Moeller series NZM connection type | |
| CATALOG NUMBER | 104643 | |
| MODEL CODE | NZM3-4-XKSFA | |
| EAN | 4015081044535 | |
| PRODUCT LENGTH/DEPTH | 82 mm | |
| PRODUCT HEIGHT | 30 mm | |
| PRODUCT WIDTH | 182 mm | |
| PRODUCT WEIGHT | 0.098 kg | |
| COMPLIANCES | IEC RoHS conform | |
| GLOBAL CATALOG | 104643 | |



| Product specification | S |
|--|--|
| USED WITH | NZM3(-4), PN3(-4), N(S)3(- 4) |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF | Does not apply, since the |

| Resources | |
|-----------------------|---|
| BROCHURES | eaton-feerum-the-whole- grain-solution-success- story-en-us.pdf |
| | eaton-digital-nzm- brochure-br013003en-en- us.pdf |
| CATALOGS | eaton-digital-nzm-catalog- ca013003en-en-us.pdf |
| DRAWINGS | eaton-circuit-breaker- terminals-nzm-terminal- cover-3d-drawing-003.eps |
| INSTALLATION VIDEOS | Introduction of the new digital circuit breaker NZM |
| | The new digital NZM Range |
| MCAD MODEL | DA-CD-nzm3 4 xksfa |
| TECHNICAL DATA SHEETS | eaton-nzm-technical- information-sheet |

| PROTECTION OF ASSEMBLIES | entire switchgear needs to be evaluated. |
|--|--|
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | ls the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | ls the panel builder's responsibility. |
| 10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH | ls the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | ls the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | ls the panel builder's responsibility. |
| FRAME | NZM3 |
| NUMBER OF POLES | Four-pole |
| ТҮРЕ | Accessory Terminal Terminal cover |
| SPECIAL FEATURES | Knockout not UL/CSA approved |
| PHASE SEPARATOR TYPE | Other |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









