

Specifications



Eaton 105853

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=120x80x95mm, +mounting rail CI-K1H-95-TS

General specifications

PRODUCT NAME	Eaton Moeller® series CI-K Insulated enclosure
CATALOG NUMBER	105853
MODEL CODE	CI-K1H-95-TS
EAN	4015081056309
PRODUCT LENGTH/DEPTH	95 mm
PRODUCT HEIGHT	137 mm
PRODUCT WIDTH	80 mm
PRODUCT WEIGHT	0.169 kg
CERTIFICATIONS	UL94: HB IEC/EN 60529 DIN EN 62208 IEC 60068-2-11 UL94: VO/1.5 mm thickness
CATALOG NOTES	Lamp indicator L-... can be mounted in base knock-out M20/M25
GLOBAL CATALOG	105853



Powering Business Worldwide

Product specifications

TYPE	Basic enclosure
FEATURES	UV resistance beneath protective shield Halogen free
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Not applicable.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF	Does not apply, since the

Resources

DECLARATIONS OF CONFORMITY	UKCA CI-K..-TS/M general purpose enclosures CE CI-K..-TS/M general purpose enclosures
DRAWINGS	eaton-insulated-boards-enclosure-ci-k-insulated-enclosure-dimensions-002.eps eaton-insulated-boards-mounting-ci-k-insulated-enclosure-dimensions.eps eaton-insulated-boards-mounting-ci-k-insulated-enclosure-dimensions-002.eps eaton-small-enclosures-device-ci-k-insulated-enclosure-3d-drawing.eps
ECAD MODEL	ETN.CI-K1H-95-TS
INSTALLATION INSTRUCTIONS	IL01502081Z
MCAD MODEL	ci_k_ts_2_DA-CD-ci_k1_ts

PROTECTION OF ASSEMBLIES	entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.
FITTED WITH:	Mounting rail to IEC/EN 60715
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
ENCLOSURE MATERIAL	Plastic $1 \Omega \times 10^{13}$ (Surface resistance to IEC 60093)
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
MOUNTING DEPTH	72 mm
MOUNTING WEIGHT CAPACITY - MAX	0.5 kg
PRODUCT CATEGORY	<ul style="list-style-type: none"> • Empty enclosures • Small enclosures
ENCLOSURE COLOR	Light gray, Operator (RAL 7035) Light gray, Cover (RAL 7035) Black (RAL 9005)
ENVIRONMENTAL RESISTANCE	Partly resistant to alcohol Not resistant to Mineral oil

Resistant against alkalis
 Not resistant to alkalis
 Not resistant to benzene
 Resistant against alcohol
 Resistant against salt solutions
 Partly resistant to greases
 Resistant against gasoline
 Partly resistant to acids (> 10%)
 Partly resistant to benzene

Resistant against greases
 Chemical resistant (Base, Cover)
 Resistant against acids (< 10%)
 Resistant against mineral oil
 Resistant against benzene
 Chemical resistant (Push-through membrane (CI-K1/CI-K2) and sealing material)

COVER MATERIAL	Glass-fiber reinforced polycarbonate
DEGREE OF PROTECTION	IP65 NEMA Other
MODEL	Surface mounting
DIELECTRIC STRENGTH	30 kV/mm, according to IEC 60243-1
DEGREE OF PROTECTION (FRONT SIDE)	IP65
TEMPERATURE RESISTANCE	-40 - 80 °C (gasket) -40 - 120 °C (enclosure)
FLAMMABILITY CHARACTERISTICS	960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2) 650 °C/1 mm thick (push-through membrane and seal material) to VDE 0471 Part 2)
KNOCKOUTS	Hard knockout version Metric cable entry knockouts at the top, bottom and back plate
IMPACT RESISTANCE	IK04 (according to EN 50102)
RADIATED HEAT DISSIPATION WITH SEPARATE MOUNTING	10 W (at an ambient temperature of 20 °C)

SURFACE TREATMENT	Resistant to corrosion
TRACK RESISTANCE	CTI 175 (cover, to IEC 60112) CTI 175 (base, to IEC 60112)
WATER CONSUMPTION	0.29 % (According to DIN EN ISO 62)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

