

Specifications



Photo is representative

Eaton 113895

Eaton Distribution parts. Auxiliary contact, for FAZ-NA, FAZ-RT, 1N/O+1N/C, 0.5HP

General specifications

PRODUCT NAME	Eaton Distribution parts
CATALOG NUMBER	113895
MODEL CODE	Z-IHK-NA
EAN	4015081134052
PRODUCT LENGTH/DEPTH	96 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	8.8 mm
PRODUCT WEIGHT	0.048 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 60898 CSA (File No. 204453) CSA-C22.2 No. 5-09 UL 489 North America (UL listed, CSA certified) CE marking CSA (Class No. 1437-01) UL (Category Control Number DIHS, DIHS7) UL (File No. E257181) EN45545-2 IEC 61373
GLOBAL CATALOG	113895

Product specifications

USED WITH	Auxiliary contacts Accessory for miniature circuit breaker Accessory
VOLTAGE RATING	250 V AC
AMPERAGE RATING	6 A
ACCESSORY/SPARE PART TYPE	Auxiliary contacts
DEGREE OF PROTECTION	IP20 (IEC) UL/CSA Type: - IP40
FRAME	Standard front dimension: 45 mm
FREQUENCY RATING	50 Hz / 60 Hz
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
MOUNTING METHOD	For fitting on left to: FAZ-NA, FAZ-RT
ADDITIONAL EQUIPMENT REQUIRED	Auxiliary switch
TERMINAL PROTECTION	Busbar tag shroud to BGV A3
TERMINAL TYPE	Lift terminals
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
ASSEMBLY WIDTH	0.5 TE
CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
ENCLOSURE WIDTH	80 mm
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF POLES AT MAIN CONTACT UNIT - MAX	2
NUMBER OF SWITCHES (FAULT SIGNAL)	0
RATED CONDITIONAL	1 kA

Resources

DECLARATIONS OF CONFORMITY	eaton-distribution-parts-declaration-of-conformity-eu250424en.pdf
DRAWINGS	1220DRW-84 eaton-dimensions-mas-z-ihk-na.jpg
ECAD MODEL	ETN.Z-IHK-NA
INSTALLATION INSTRUCTIONS	eaton-auxiliary-switch-z-ihk-na-instruction-leaflet-il019018zu.pdf
MCAD MODEL	z_ihk_na.dwg z_ihk_na.stp
WIRING DIAGRAMS	ZP_IHK_1220SWI-1

SHORT-CIRCUIT CURRENT (IQ) WITH 6 A BACK-UP FUSE	
RATED INSULATION VOLTAGE (UI)	250 VAC
VOLTAGE TYPE	AC
FUNCTIONS	Auxiliary switch
CONTACT FUNCTION	1 M + 1 B
DEVICE FITTING	Miniature circuit breaker (MCB)
TYPE	• Accessory • Accessory for miniature circuit breaker
APPLICATION	Switchgear for export to North America (UL-listed)
MOUNTING WIDTH	8.8 mm (0.5 space units)
RATED OPERATIONAL VOLTAGE (UE) - MAX	250 V
RATED SWITCH CURRENT	6 A
SUITABLE FOR CURRENT OF MAIN CONTACT UNIT - MAX	6 A
VOLTAGE RATING PER CONTACT - MIN	5 VDC
RATED OPERATIONAL CURRENT	0.5 A (110 V DC-13) 2 A (250 V AC-15) 3 A (250 V AC-12)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

