## Specifications



## Eaton 115365

Eaton Moeller series NZM - Molded Case Circuit Breaker. Label, +symbol disconnector

General specifications	
PRODUCT NAME	Eaton Moeller series NZM operating element accessory
CATALOG NUMBER	115365
MODEL CODE	ZFS-TS-NZM
EAN	4015081151363
PRODUCT LENGTH/DEPTH	64 mm
PRODUCT HEIGHT	5 mm
PRODUCT WIDTH	27 mm
PRODUCT WEIGHT	0.004 kg
COMPLIANCES	UL/CSA IEC RoHS conform
GLOBAL CATALOG	115365



Product specification	S
USED WITH	NZM1(-4), PN1(-4), N(S)1(-4) NZM1 NZM2-4 NZM3 N2 NZM1-4 N1 N2-4 N3 N4 NZM4(-4), N(S)4(-4) NZM4-4 N1-4 N3-4 NS1 NS3 NZM3-NA NZM2(-4), PN2(-4), N(S)2(-4) NZM3-4 NZM4 PN1 PN2 PN3 N4-4 NS2 NZM1-NA NZM2 PN2-4 NS4 NZM2-NA NZM2-NA NZM2-NA NZM3(-4), PN3(-4), N(S)3(-4) NZM3-NA NZM3(-4), PN3(-4), N(S)3(-4) NZM4-NA PN1-4 PN3-4
FEATURES	Waterproof
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be

observed.

The device meets the

requirements, provided

**10.13 MECHANICAL** 

**FUNCTION** 

Resources	
BROCHURES	eaton-digital-nzm- brochure-br013003en-en- us.pdf
	eaton-feerum-the-whole- grain-solution-success- story-en-us.pdf
CATALOGS	eaton-digital-nzm-catalog- ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-nzm- warning-plate-3d- drawing.eps
INSTALLATION VIDEOS	The new digital NZM Range
	Introduction of the new digital circuit breaker NZM
TECHNICAL DATA SHEETS	<u>eaton-nzm-technical-</u> <u>information-sheet</u>

	the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

COLOR	Silver
FITTED WITH:	Alert/Information symbol Mounting material
FRAME	NZM1/2/3/4
MOUNTING METHOD	Other
MATERIAL QUALITY	Other
OUTER DIAMETER	0 mm
LANGUAGE OF THE IMPRINT	Other
MEANING OF THE IMPRINT	Other
MODEL	Other
SYMBOL	Other
THICKNESS OF WARNING LABEL	5 mm
ACCESSORY SHAPE	Rectangular
MATERIAL	Plastic
ТҮРЕ	Accessory External warning plate
INSCRIPTION	Symbol disconnectors

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



**Eaton Corporation plc** Eaton House 30 Pembroke Road

Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









