

Specifications



Photo is representative



Eaton 115974

Eaton Moeller® series M22 Function element, for combination with RMQ-Titan operating elements M22-..., 1 changeover contact, Front fixing, green

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Function element
CATALOG NUMBER	115974
MODEL CODE	M22-SWD-K11LED-G
EAN	4015081157143
PRODUCT LENGTH/DEPTH	45 mm
PRODUCT HEIGHT	42 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	0.009 kg
CERTIFICATIONS	CSA File No.: 2324643 IEC/EN 61131-2 CSA EN 50178 UL Category Control No.: NKCR UL UL File No.: E29184 CSA Class No.: 3211-07 BV LRS
GLOBAL CATALOG	115974

Product specifications

AIR DISCHARGE	8 kV, according to IEC 61131-2, level 3, ESD
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF	Does not apply, since the

Resources

CATALOGS	eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf Flip catalog - Product Range Catalog - Command and indication
CONTROL TRAVEL DIAGRAM	eaton-operating-diagram-m22-contact-element-contact-travel-diagram-009.eps
DECLARATIONS OF CONFORMITY	eaton-function-element-declaration-of-conformity-eu250506en.pdf
DRAWINGS	2723DIM-25 eaton-operating-function-m22-function-element-dimensions.eps eaton-operating-m22-function-element-3d-drawing-004.eps eaton-operating-button-symbol-004.eps
ECAD MODEL	ETN.115974.edz
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL04716004Z2021_10.pdf
INSTALLATION VIDEOS	RMQ Flat Design
MANUALS AND USER GUIDES	MN05006002Z_EN MN05006001Z_EN
MCAD MODEL	funktionselement k11_led_front funktionselement k11_led_front.stp
MULTIMEDIA	RMQ small E-Stop emergency-stop button MCI MultiColor Light Indicator RMQ compact solution MCI Multicolor Light Indicator M22 with SmartWire-DT easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

PROTECTION OF ASSEMBLIES	entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
ELECTRIC CONNECTION TYPE	Flat plug-in connection
POLLUTION DEGREE	2
BURST IMPULSE	1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3 2 kV, Supply cable, according to IEC/EN 61131-2, Level 3
ADDRESSING	Address set automatically
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

SALES NOTES	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
	eaton-control-circuit-devices-rmq-titan-fl144090en-en-us.pdf
	eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf
	eaton-rmq-chemical-resistance-flyer-fl047011en-en-us.pdf
	eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf
WIRING DIAGRAMS	eaton-modular-plc-m22-function-element-wiring-diagram-003.eps
	eaton-modular-plc-m22-function-element-wiring-diagram.eps

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF SWITCHES (FAULT SIGNAL)	0
CONNECTION TO SMARTWIRE-DT	Yes
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
MOUNTING POSITION	As required
CONNECTION TYPE	Front fixing SWD: Plug, 8-pole
MOUNTING METHOD	Front fastening
CONNECTION	SmartWire-DT plug connector SWD4-8SF2-5
CONTACT DISCHARGE	4 kV, according to IEC/EN 61131-2, Level 2, ESD
OVERVOLTAGE CATEGORY	Not applicable
DEGREE OF PROTECTION	IP20
CONSTANT ACCELERATION	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
MODEL	Top mounting
CONSTANT AMPLITUDE	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
LAMP HOLDER	LED not exchangeable
FUNCTIONS	For combination with RMQ-Titan operating elements M22-... Diagnosis function
ELECTROMAGNETIC FIELDS	1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008) 10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN

	61131-2:2008)
RADIATED RFI	10 V (IEC/EN 61131-2:2008, Level 3)
DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
RADIO INTERFERENCE CLASS	Class A (EN 55011)
RELATIVE HUMIDITY	9 - 95 % (non-condensing, IEC/EN 60068-2-30)
LED INDICATOR	Status indication of SmartWire-DT network: Green LED Status indication of Switching state: Yellow LED
STATION	SmartWire-DT slave, SmartWire-DT network
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0.3 W
PRODUCT CATEGORY	SmartWire-DT RMQ connections
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	0 A
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

