

# Specifications



Photo is representative

## Eaton 118905

Eaton Moeller series NZM - Molded Case Circuit Breaker. Connection block for adapter top 4p, size 2

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series NZM multi-function device adapter
<b>CATALOG NUMBER</b>	118905
<b>MODEL CODE</b>	+NZM2-4-XKR4O
<b>EAN</b>	4015081171040
<b>PRODUCT LENGTH/DEPTH</b>	136 mm
<b>PRODUCT HEIGHT</b>	35 mm
<b>PRODUCT WIDTH</b>	93 mm
<b>PRODUCT WEIGHT</b>	0.2 kg
<b>COMPLIANCES</b>	IEC RoHS conform
<b>CERTIFICATIONS</b>	Specially designed for North America UL listed CE marking IEC60947-2 CSA-C22.2 No. 5-09 UL (File No. E31593) CSA (File No. 22086) CSA (Class No. 1432-01) UL (Category Control Number DIVQ) UL489 CSA certified

## Product specifications

<b>USED WITH</b>	NZM2-4 N(S)2-4 PN2-4 Feeder circuits, branch circuits
<b>AMPERAGE RATING</b>	250 A
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.

## Resources

<b>BROCHURES</b>	<a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a> <a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a>
<b>CATALOGS</b>	<a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-03 NZM2</a>
<b>DRAWINGS</b>	<a href="#">eaton-circuit-breaker-nzm-connection-block-3d-drawing.eps</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">eaton-circuit-breakers-nzm2-xkr-o-u-rear-connection-instruction-leaflet-il01219047z.pdf</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">The new digital NZM Range</a> <a href="#">Introduction of the new digital circuit breaker NZM</a>
<b>MCAD MODEL</b>	<a href="#">DA-CS-nzm2_4_xkr4_o_u</a> <a href="#">DA-CD-nzm2_4_xkr4_o_u</a>
<b>TECHNICAL DATA SHEETS</b>	<a href="#">eaton-nzm-technical-information-sheet</a>

<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FRAME</b>	NZM2
<b>SUITABLE FOR</b>	Four-pole
<b>VOLTAGE RATING (UL CSA 13)</b>	Max. 480 Y / 277 V
<b>DEGREE OF PROTECTION</b>	IP20
<b>MOUNTING POSITION</b>	Fitted above
<b>NUMBER OF POLES</b>	Four-pole
<b>MODEL</b>	Other
<b>TYPE</b>	60 mm system Accessory Accessory, multifunction component adapter Connection block Connection block for component adapter
<b>SPECIAL FEATURES</b>	Current limiting circuit breaker For NZM2 component adapter, connection at top

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

