

# CRIMPFOX-M RCI 6/DIE - Crimp insert



1212073

<https://www.phoenixcontact.com/pc/products/1212073>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Die, for Crimpfox-M, for insulated cable lugs 0.1 - 0.4 mm<sup>2</sup> and 4 - 6 mm<sup>2</sup> (light green, yellow), packed in a serial storage box

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1212073             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Product key                          | BH313Y              |
| Catalog page                         | Page 436 (C-3-2019) |
| GTIN                                 | 4046356452526       |
| Weight per piece (including packing) | 80.8 g              |
| Weight per piece (excluding packing) | 80.4 g              |
| Customs tariff number                | 82032000            |
| Country of origin                    | DE                  |

# CRIMPFOX-M RCI 6/DIE - Crimp insert



1212073

<https://www.phoenixcontact.com/pc/products/1212073>

## Technical data

### Product properties

|              |            |
|--------------|------------|
| Product type | Die        |
| Compression  | Oval crimp |

#### Crimping position 1

|                    |                     |
|--------------------|---------------------|
| Min. cross section | 0.1 mm <sup>2</sup> |
| Max. cross section | 0.4 mm <sup>2</sup> |
| AWG min            | 26                  |
| AWG max            | 22                  |

#### Crimping position 2

|                    |                   |
|--------------------|-------------------|
| Min. cross section | 4 mm <sup>2</sup> |
| Max. cross section | 6 mm <sup>2</sup> |
| AWG min            | 12                |
| AWG max            | 10                |

### Connection data

#### Conductor connection

|                             |                                           |
|-----------------------------|-------------------------------------------|
| Cross section range, metric | 0.1 mm <sup>2</sup> ... 6 mm <sup>2</sup> |
|-----------------------------|-------------------------------------------|

### Dimensions

|        |         |
|--------|---------|
| Width  | 75 mm   |
| Height | 25.5 mm |
| Length | 114 mm  |

### Material specifications

|       |       |
|-------|-------|
| Color | black |
|-------|-------|

# CRIMPFOX-M RCI 6/DIE - Crimp insert



1212073

<https://www.phoenixcontact.com/pc/products/1212073>

## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1212073>



**EAC**

Approval ID: RU x-DE.xx08.B.02974

# CRIMPFOX-M RCI 6/DIE - Crimp insert



1212073

<https://www.phoenixcontact.com/pc/products/1212073>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 21049090 |
| ECLASS-12.0 | 21049090 |
| ECLASS-13.0 | 21043892 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001282 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 27111500 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)