#### 1212258

https://www.phoenixcontact.com/us/products/1212258

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Automatic stripping device with integrated graphic display, for conductors and cables up to 6 mm in diameter, 120 V version

#### Your advantages

- Multi-strand cables with a diameter of up to 6 mm can also be stripped
- · The stripping dimensions are set individually via knobs and are shown on the large display
- · Partial stripping is supported
- · The clamping force automatically adjusts itself to the required extraction force
- Compact automatic stripping device for automatically stripping conductors with a cross-section of 0.08 mm<sup>2</sup> to 6 mm<sup>2</sup>
- · Pressure points on sensitive insulation are avoided
- · Even special types of insulation, such as PTFE and silicone, can be stripped in addition to standard types

#### Commercial data

Item number	1212258
item number	1212258
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH32
Product key	BH3221
Catalog page	Page 407 (C-3-2019)
GTIN	4046356457019
Weight per piece (including packing)	99.99 g
Weight per piece (excluding packing)	11,092 g
Customs tariff number	84798100
Country of origin	DE

PHŒN

1212258

https://www.phoenixcontact.com/us/products/1212258

### Technical data

#### Product properties

Product type	Automatic stripping device
Partial stripping length	2 mm 20 mm
Insertion length minimum	15 mm
Maximum throughput	6
Min. cross section	0.08 mm <sup>2</sup>
Ma and a second and	0
Max. cross section	6 mm <sup>2</sup>
ectrical properties	60 Hz
ectrical properties Frequency range	60 Hz
Exercised properties Frequency range Power consumption	60 Hz 160 VA

#### Connection data

Conductor connection

Cross section range, metric	0.08 mm² 6 mm²
Cross section range AWG	28 10
Stripping length	2 mm 20 mm

#### Dimensions

Width	141 mm
Height	221 mm
Length	363 mm
Diameter	6 mm
Diameter, conductor entry opening	6 mm
External dimensions	
Outside diameter	6 mm

External cable diameter	≤ 6.00 mm

PHŒN

IX

1212258

https://www.phoenixcontact.com/us/products/1212258

#### Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1212258

EAC Approval ID: RU C-DE.AI30.B.01549



1212258

https://www.phoenixcontact.com/us/products/1212258



### Classifications

#### ECLASS

ECLASS-11.0	17130102
ECLASS-12.0	17130102
ECLASS-13.0	17130102

#### ETIM

	ETIM 9.0	EC002778
UN	UNSPSC	
	UNSPSC 21.0	27111500

1212258

https://www.phoenixcontact.com/us/products/1212258



### Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

1212258

https://www.phoenixcontact.com/us/products/1212258



Accessories

WF 1000/CJ - Replacement retaining jaw

1212415 https://www.phoenixcontact.com/us/products/1212415

Replacement jaws, for automatic stripping device



WF 1000/TR - Accessories for tools/automatic devices

1212416 https://www.phoenixcontact.com/us/products/1212416

Start button trigger, for automatic stripping device



1212258

https://www.phoenixcontact.com/us/products/1212258



WF 1000/SB - Spare knife

#### 1212279

https://www.phoenixcontact.com/us/products/1212279

Replacement blade, for automatic stripping device



#### WF 1000/CJ - Replacement retaining jaw

1212415 https://www.phoenixcontact.com/us/products/1212415

Replacement jaws, for automatic stripping device



1212258

https://www.phoenixcontact.com/us/products/1212258

#### WF 1000/COV - Accessories for tools/automatic devices

1212417

https://www.phoenixcontact.com/us/products/1212417

Receptacle tray, for automatic stripping device



#### WF 1000/TR - Accessories for tools/automatic devices

1212416 https://www.phoenixcontact.com/us/products/1212416

Start button trigger, for automatic stripping device



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com PHŒN