

1212578

https://www.phoenixcontact.com/us/products/1212578

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Screw bit, $Torx^{\$}$, E6.3-1/4" drive, size: TX 20 x 50 mm, hardened, suitable for holder according to DIN 3126-F6.3/ISO 1173

Your advantages

• Tools for SF-ASD 21 cordless screwdriver in various versions

Commercial data

Item number	1212578
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BH31
Product key	BH3149
Catalog page	Page 457 (C-3-2019)
GTIN	4046356590136
Weight per piece (including packing)	8.94 g
Weight per piece (excluding packing)	8.94 g
Customs tariff number	82079030
Country of origin	CZ



https://www.phoenixcontact.com/us/products/1212578



Technical data

Notes

"Downloads" in the manufacturer's declaration			
Torx			
Screwdriver tools			
Torx [®]			
50 mm			
50 mm			
Material specifications			
silver			
alloyed tool steel			



https://www.phoenixcontact.com/us/products/1212578



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1212578



EAC

Approval ID: RU C-DE.Al30.B.01750



1212578

https://www.phoenixcontact.com/us/products/1212578

Classifications

ECLASS

	ECLASS-11.0	21044290		
	ECLASS-12.0	21044290		
	ECLASS-13.0	21044202		
ETIM				
	ETIM 9.0	EC011813		
UNSPSC				
	UNSPSC 21.0	27111700		



https://www.phoenixcontact.com/us/products/1212578



Mandatory accessories

SF-M BH - Screwdriver

1212070

https://www.phoenixcontact.com/us/products/1212070



Bit screwdriver, with 1/4" quick-action chuck, handle length 119 mm, 2-component handle, with non-slip grip, suitable for bits according to DIN 3126-C 6.3 and E 6.3/ISO 1173, magnetic

SF-ASD 16 SET - Battery-powered screwdriver set

1200295

https://www.phoenixcontact.com/us/products/1200295



Cordless screwdriver in case, incl. battery, charging device $100 \dots 240 \text{ V}$, 2 bits, two-speed gearbox, forward/reverse running and 16-stage clutch up to 450 rpm, hexagonal fast connection.

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com