



PRODUCT-DETAILS

1265-85-MN

1265-85-MN Surge Protector



General Information	
Global Commercial Alias	1265-85-MN
Extended Product Type	1265-85-MN
Product ID	7TAA183030R0003
EAN	786210051246
Catalog Description	1265-85-MN Surge Protector
Long Description	Heavy duty service entrance applications 240 kA SURGE PROTECT.120/240V

Technical	
Rated Voltage (U_r)	120 V AC
Voltage Protection Level (U_p)	(N-PE) 1 kV
Maximum Continuous Operating Voltage (U_c)	(L-PE) 150 V
Rated Service Short-Circuit Breaking Capacity (I_{cs})	100 kA
Discharge Current	Nominal (8 / 20 μ s) 20 kA I (max, 8 / 20 μ s) 240 kA
Number of Protected	3

Poles	
Number of Conductors	3
Transmission Standard	Optic
Mounting Type	Wall Mounting

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
---	-----------------

Dimensions

Product Net Width	276.9 mm
Product Net Height	342.9 mm
Product Net Depth / Length	132.1 mm
Product Net Weight	10.0 kg

Ordering

EAN	786210051246
-----	--------------

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Installation

Instructions and Manuals	750-0111-001
--------------------------	--------------

Popular Downloads

Data Sheet, Technical Information	BRO-SURG-1265M-MK-9020
-----------------------------------	------------------------

External Classifications and Standards

ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	Product Not in WEEE Scope
eClass	V11.0 : 27130805

Additional Information

Product Main Type	1265
-------------------	------

Categories

Low Voltage Products and Systems → Surge Protective Devices → UL standard → Hardwired and Wall Mount

