

# Specifications

Photo is representative

## Eaton 134937

Eaton DS7 Soft starter, 81 A, 200 - 480 V AC,  
Us= 110 - 230 V AC, Frame size FS3

### General specifications

<b>PRODUCT NAME</b>	Eaton DS7 Soft starter
<b>CATALOG NUMBER</b>	134937
<b>MODEL CODE</b>	DS7-342SX081N0-N
<b>EAN</b>	4015081317523
<b>PRODUCT LENGTH/DEPTH</b>	139 mm
<b>PRODUCT HEIGHT</b>	175 mm
<b>PRODUCT WIDTH</b>	93 mm
<b>PRODUCT WEIGHT</b>	1.8 kg
<b>CERTIFICATIONS</b>	IEC/EN 60947-4-2 UL 508 C-Tick CSA22.2-14 CSA File No.: 2511305 CSA-C22.2 No 14-05 CE CSA Class No.: 321106 CSA-C22.2 No 0-M91 CSA UkrSEPRO UL UL File No.: E251034 GB 14048.6
<b>GLOBAL CATALOG</b>	134937

## Product specifications

<b>CONTROL VOLTAGE</b>	110/230 Vac control
<b>PHASE</b>	Three-phase
<b>SPECIAL FEATURES</b>	Internal bypass
<b>TYPE</b>	Soft starter for three-phase loads
<b>VOLTAGE RATING</b>	110/230 V
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to

## Resources

<b>BROCHURES</b>	<a href="#">eaton-softstarter-s811-ds7-brochure-br039001en-en-us.pdf</a>
<b>CATALOGS</b>	<a href="#">Product Range Catalog Drives Engineering</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00003978.pdf</a> <a href="#">DA-DC-00004193.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-semiconductor-contactors-softstarter-ds7-dimensions-002.eps</a> <a href="#">eaton-semiconductor-contactors-softstarter-ds7-3d-drawing-005.eps</a>
<b>ECAD MODEL</b>	<a href="#">DA-CE-ETN.DS7-342SX081N0-N</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL03902005Z2021_06.pdf</a>
<b>MANUALS AND USER GUIDES</b>	<a href="#">eaton-ds7-soft-starter-mn03901001z-en-us.pdf</a>
<b>MCAD MODEL</b>	<a href="#">eaton-low-voltage-soft-starters-3d-models-ds7-3-100316.stp</a> <a href="#">eaton-low-voltage-soft-starters-drawings-ds7-3-100316.dwg</a>
<b>MULTIMEDIA</b>	<a href="#">Soft starter DS7 up to 200 A</a>

	be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FITTED WITH:</b>	Internal bypass Internal bypass contacts
<b>POLLUTION DEGREE</b>	2
<b>CLASS</b>	Other
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>FRAME SIZE</b>	FS3
<b>ALTITUDE</b>	Above 1000 m with 1 % derating per 100 m Max. 2000 m
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-5 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT STORAGE</b>	-25 °C

<b>TEMPERATURE - MIN</b>	
<b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE</b>	25 HP
<b>ASSIGNED MOTOR POWER AT 220/230 V, 60 HZ, 3-PHASE</b>	30 HP
<b>ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE</b>	60 HP
<b>EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID</b>	18 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID</b>	0 W
<b>MAINS VOLTAGE - MAX</b>	480 V
<b>MAINS VOLTAGE - MIN</b>	200 V
<b>SERIES</b>	Generation 7
<b>OUTPUT VOLTAGE</b>	250 V AC (relay outputs)
<b>NUMBER OF OUTPUTS</b>	2 Relay Outputs (TOR, Ready)
<b>SCREWDRIVER SIZE</b>	0.6 x 3.5 mm, Terminal screws, Control circuit cables PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver
<b>VOLTAGE TYPE</b>	AC
<b>RATED OPERATIONAL VOLTAGE (UE) - MIN</b>	230 V
<b>RATED POWER THREE- PHASE MOTOR, INLINE, AT 230 V</b>	22 kW
<b>RATED POWER THREE- PHASE MOTOR, INLINE, AT 400 V</b>	45 kW
<b>RATED POWER THREE- PHASE MOTOR, INSIDE DELTA, AT 230 V</b>	0 kW
<b>RATED POWER THREE- PHASE MOTOR, INSIDE DELTA, AT 400 V</b>	0 kW
<b>STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS</b>	18 W

<b>VOLTAGE RATING - MAX</b>	480 V
<b>APPLICATION</b>	<ul style="list-style-type: none"> <li>• 1-phase motors: No</li> <li>• 3-phase motors: Yes</li> <li>• Soft starting of three-phase asynchronous motors</li> </ul>
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact
<b>MOUNTING POSITION</b>	Vertical
<b>INPUT CURRENT</b>	4 mA (at 230 V AC, Digital inputs)
<b>DROP-OUT VOLTAGE</b>	AC operated: 0 - 15 V, AC operated
<b>OVERVOLTAGE CATEGORY</b>	II
<b>DEGREE OF PROTECTION</b>	NEMA 1 IP20
<b>CURRENT CONSUMPTION</b>	<p>0,6 A/50 ms, Control circuit, Regulator supply at peak performance (close bypass) at 24 V DC</p> <p>1.6 mA, Control circuit, Digital inputs, External 24 V</p> <p>50 mA, Control circuit, Regulator supply</p>
<b>FUNCTIONS</b>	<p>Potential isolation between power and control sections</p> <p>Single direction</p> <p>Min. ramp time 1 s - fast switching (semiconductor contactor)</p> <p>Suppression of closing transients</p> <p>Suppression of DC components for motors</p> <p>Soft start function</p>
<b>DELAY TIME</b>	0 - 30 s, Soft start function, Ramp times
<b>OVERLOAD CYCLE</b>	AC-53a: 3 - 5: 75 - 10
<b>DROP-OUT TIME</b>	350 ms, Control circuit, Digital Inputs, AC operated
<b>PICK-UP VOLTAGE</b>	108 - 253 V AC
<b>RADIO INTERFERENCE CLASS</b>	Class A (EN 55011)

<b>PICK-UP TIME</b>	250 ms at AC
<b>RATED CONTROL VOLTAGE (UC)</b>	110 - 230 V AC 110 - 230 V AC (-15 %/+10 %)
<b>SUPPLY FREQUENCY</b>	50/60 Hz, fLN, Main circuit
<b>TERMINAL CAPACITY (STRANDED)</b>	1 x (0.5 - 1.5) mm <sup>2</sup> , Control circuit cables 2 x (6 - 25) mm <sup>2</sup> , Main cables 1 x (25 - 70) mm <sup>2</sup> , Main cables 2 x (0.5 - 1.0) mm <sup>2</sup> , Control circuit cables
<b>TERMINAL CAPACITY (COPPER BAND)</b>	2 x 9 x 0.8 mm, Main cables 9 x 9 x 0.8 mm, Main cables
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	230 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	110 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	230 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	110 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	0 V
<b>RATED OPERATIONAL CURRENT (IE) AT AC-11</b>	1 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-53</b>	81 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	81 A
<b>RATED OPERATIONAL POWER AT 220/230 V, 50 HZ</b>	22 kW
<b>RATED OPERATIONAL POWER AT 400 V, 50 HZ</b>	45 kW
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	480 V
<b>VIBRATION RESISTANCE</b>	2M2 to EN 60721-3-2

<b>RAMP/RUN-UP TIME</b>	1 - 30 s
<b>SHOCK RESISTANCE</b>	8 g, 11 ms, Mechanical
<b>SUITABLE FOR</b>	Branch circuits, (UL/CSA)
<b>TIGHTENING TORQUE</b>	9 Nm (> 10 mm <sup>2</sup> ) 0.4 Nm, Screw terminals, Control circuit cables 6 Nm (≤ 10 mm <sup>2</sup> )
<b>SHORT-CIRCUIT PROTECTION RATING</b>	3 x 170M4008, Type „2“ coordination (additional with the fuses for coordination type „1“), Main conducting paths NZMN1-M100, Type “1” coordination, Main conducting paths
<b>START VOLTAGE</b>	Min. 30 %, Soft start function, Start voltage = turn-off voltage Max. 100 %, Soft start function, Start voltage = turn-off voltage
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	2 x (0.5 - 0.75) mm <sup>2</sup> , Control circuit cables 1 x (0.5 - 1.5) mm <sup>2</sup> , Control circuit cables
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.5 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (0.5 - 1.0) mm <sup>2</sup> , Control circuit cables 2 x (6 - 25) mm <sup>2</sup> , Main cables 1 x (25 - 70) mm <sup>2</sup> , Main cables
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	1 x (12 - 2/0), Main cables 1 x (21 - 14), Control circuit cables 2 x (21 - 18), Control circuit cables

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

