

Specifications

Eaton 135814

Eaton Moeller® series E55 Proximity switch, inductive, 1N/O/1N/C, Sn=30mm, 2L, 35-250VAC, quad.40, insulated material, screw connection

General specifications

PRODUCT NAME	Eaton Moeller® series E55 Proximity switch
CATALOG NUMBER	135814
MODEL CODE	E55BLT1E
EAN	4015081326075
PRODUCT LENGTH/DEPTH	152.4 mm
PRODUCT HEIGHT	44.45 mm
PRODUCT WIDTH	152.4 mm
PRODUCT WEIGHT	0.23 kg
CERTIFICATIONS	CE IEC/EN 60947-5-2



Powering Business Worldwide

Product specifications

TYPE	Inductive sensor
ELECTRIC CONNECTION TYPE	Clamp
ENCLOSURE MATERIAL FINISHING	Other
ACTUATION TYPE	Metallic Target
ENCLOSURE MATERIAL	Plastic
ENCLOSURE TYPE	Cuboid
CATEGORY (EN 954-1)	B
EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
SAFETY PERFORMANCE LEVEL (EN ISO 13849-1)	None
SIL (IEC 61508)	None
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
DIAMETER SENSOR	0 mm
NUMBER OF CONTACT ENERGIZED OUTPUTS WITH SIGNALLING FUNCTION	0
NUMBER OF CONTACTS (PROGRAMMABLE)	1
NUMBER OF OUTPUTS (PROTECTED CONTACT ENERGIZED)	0
NUMBER OF OUTPUTS (PROTECTED SEMICONDUCTOR)	0
NUMBER OF OUTPUTS (SEMICONDUCTOR WITH SIGNALING FUNCTION)	1
OPERATIONAL CURRENT (IB) IN THE SWITCHED STATE AT 24 V DC	3 A
OUTPUT CURRENT AT PROTECTED OUTPUT - MAX	0 mA
RATED CONTROL SUPPLY VOLTAGE (US)	250 V

Resources

CATALOGUES	Product Range Catalog Sensors – products, basic information, applications
DECLARATIONS OF CONFORMITY	DA-DC-00004656.pdf DA-DC-00004651.pdf
DRAWINGS	eaton-proximity-switches-inductive-sensor-e55-proximity-switch-dimensions.eps eaton-proximity-switches-e55-proximity-switch-3d-drawing.eps
INSTALLATION INSTRUCTIONS	IL05301006Z
MULTIMEDIA	We make what matters

AT AC, 50 HZ - MAX	
FUNCTIONS	Protection against polarity reversal Short-circuit protection Protection against wire breakage
VOLTAGE TYPE	AC
MOUNTING METHOD	Non-flush mounting
MATERIAL	Insulated material
CONNECTION TYPE	2-wire Screw terminal
INSTALLATION TYPE	Not flat
DEGREE OF PROTECTION	IP67 NEMA 4X, 6, 13
INTERFACE TYPE	None
LED INDICATOR	Status indication of Operating voltage: Green LED Status indication of Switching state: Red LED
SWITCH FUNCTION TYPE	Programmable/configurable
LOAD CURRENT	Max. 400 mA (I _e)
RESIDUAL CURRENT	1.8 mA (through the load in the blocked state at 230 V AC and 24 V DC)
RESIDUAL RIPPLE	10 % (U _e)
SHOCK RESISTANCE	30 g, Mechanical, Shock duration 11 ms
SUPPLY FREQUENCY	60 Hz, Input, max. Range 50 Hz, Input, min. Range
SWITCHING FREQUENCY	25 Hz
VOLTAGE RATING - MAX	250 V
WIDTH SENSOR	40 mm
PRODUCT CATEGORY	E55 Limit Switch Style Series
SWITCHING OUTPUT TYPE	Two-wire
TEMPERATURE DRIFT OF SN	10 %
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	35 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	250 V
RATED CONTROL SUPPLY VOLTAGE (US)	35 V

AT AC, 60 HZ - MIN	
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
RATED SWITCHING DISTANCE (SN) - MAX	30 mm
REPEATABILITY	10 %
SENSOR HEIGHT	40 mm
SENSOR LENGTH	118 mm
SUPPLY VOLTAGE - MAX	250 V
SUPPLY VOLTAGE - MIN	35 V
SWITCHING HYSTERESIS OF SN	20 %
VOLTAGE DROP (UD)	8 V

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

