

# Specifications

## Eaton 135988



Eaton Moeller® series E57 Proximity switch, E57 Premium+ Series, 1 NC, 3-wire, 6 - 48 V DC, M30 x 1 mm, Sn= 22 mm, Semi-shielded, PNP, Stainless steel, 2 m connection cable

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series E57 Proximity switch
<b>CATALOG NUMBER</b>	135988
<b>MODEL CODE</b>	E57-30LE22-B1
<b>EAN</b>	4015081327812
<b>PRODUCT LENGTH/DEPTH</b>	152.4 mm
<b>PRODUCT HEIGHT</b>	50.8 mm
<b>PRODUCT WIDTH</b>	127 mm
<b>PRODUCT WEIGHT</b>	0.09 kg
<b>CERTIFICATIONS</b>	CSA Class No.: none None IEC/EN 60947-5-2 CSA File No.: none

## Product specifications

<b>TYPE</b>	Inductive sensor
<b>ELECTRIC CONNECTION TYPE</b>	Cable
<b>ENCLOSURE MATERIAL FINISHING</b>	Other
<b>ACTUATION TYPE</b>	Metallic Target
<b>ENCLOSURE MATERIAL</b>	Metal
<b>ENCLOSURE TYPE</b>	Cylinder, screw-thread
<b>CATEGORY (EN 954-1)</b>	B
<b>EXPLOSION SAFETY CATEGORY FOR DUST</b>	None
<b>EXPLOSION SAFETY CATEGORY FOR GAS</b>	None
<b>SAFETY PERFORMANCE LEVEL (EN ISO 13849-1)</b>	None
<b>SIL (IEC 61508)</b>	None
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>DIAMETER SENSOR</b>	30 mm
<b>NUMBER OF CONTACT ENERGIZED OUTPUTS WITH SIGNALLING FUNCTION</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	1
<b>NUMBER OF OUTPUTS (PROTECTED CONTACT ENERGIZED)</b>	0
<b>NUMBER OF OUTPUTS (PROTECTED SEMICONDUCTOR)</b>	0
<b>NUMBER OF OUTPUTS (SEMICONDUCTOR WITH SIGNALING FUNCTION)</b>	1
<b>OPERATIONAL CURRENT (IB) IN THE SWITCHED STATE AT 24 V DC</b>	10 A
<b>OUTPUT CURRENT AT PROTECTED OUTPUT - MAX</b>	0 mA
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	0 V

## Resources

<b>BROCHURES</b>	<a href="#">eaton-sensors-brochure-br053001en-en-us.pdf</a>
<b>CATALOGUES</b>	<a href="#">Product Range Catalog Sensors – products, basic information, applications</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004656.pdf</a> <a href="#">DA-DC-00004651.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-proximity-switches-e57-proximity-switch-dimensions.eps</a> <a href="#">1360DRW-93</a>
<b>ECAD MODEL</b>	<a href="#">DA-CE-ETN.E57-30LE22-B1</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL05301003Z</a>
<b>MULTIMEDIA</b>	<a href="#">We make what matters</a>

<b>VOLTAGE TYPE</b>	DC
<b>MOUNTING METHOD</b>	Semi-shielded mounting
<b>MATERIAL</b>	Stainless steel
<b>CONNECTION TYPE</b>	3-wire 2 m connection cable
<b>INSTALLATION TYPE</b>	Not flat
<b>DEGREE OF PROTECTION</b>	IP67 NEMA 4X, 6, 13
<b>INTERFACE TYPE</b>	None
<b>LED INDICATOR</b>	Status indication of Switching state: Red LED
<b>SWITCH FUNCTION TYPE</b>	Breaker contact
<b>LOAD CURRENT</b>	Max. 500 mA (I <sub>e</sub> , at 6 - 30 V DC)
<b>RESIDUAL CURRENT</b>	0.1 mA (through the load in the blocked state at 230 V AC and 24 V DC)
<b>SHOCK RESISTANCE</b>	30 g, Mechanical, Shock duration 11 ms
<b>SWITCHING FREQUENCY</b>	300 Hz
<b>VOLTAGE RATING - MAX</b>	48 V
<b>WIDTH SENSOR</b>	0 mm
<b>PRODUCT CATEGORY</b>	E57 Premium+ Series
<b>SWITCHING OUTPUT TYPE</b>	PNP
<b>TEMPERATURE DRIFT OF SN</b>	10 %
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	48 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	6 V
<b>RATED SWITCHING DISTANCE (SN) - MAX</b>	22 mm
<b>REPEATABILITY</b>	3 %
<b>SENSOR HEIGHT</b>	0 mm

SENSOR LENGTH	67.8 mm
SUPPLY VOLTAGE - MAX	48 V
SUPPLY VOLTAGE - MIN	6 V
SWITCHING HYSTERESIS OF SN	15 %
VOLTAGE DROP (UD)	2.5 V

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

