

# Specifications

## Eaton 136265



Eaton Moeller® series CSAS Connection cable, 3p, AC, coupling M12 flat, open end, L=2m

### General specifications

|                             |   |
|-----------------------------|---|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series<br>CSAS Accessory<br>Connection cable |
| <b>CATALOG NUMBER</b>       | 136265  |
| <b>MODEL CODE</b>           | CSAS3F3CY2202   |
| <b>EAN</b>                  | 4015081330584   |
| <b>PRODUCT LENGTH/DEPTH</b> | 165.1 mm  |
| <b>PRODUCT HEIGHT</b>       | 12.7 mm   |
| <b>PRODUCT WIDTH</b>        | 165.1 mm  |
| <b>PRODUCT WEIGHT</b>       | 0.09 kg   |
| <b>CERTIFICATIONS</b>       | CE  |

## Product specifications

|   |   |
|---|---|
| <b>TYPE</b>   | Connecting cables   |
| <b>NUMBER OF POLES</b>  | Three-pole  |
| <b>CABLE TYPE</b>   | Cable end, open, Output side<br>Multi-core Coupling, straight, Input side |
| <b>CONTACT SURFACE MATERIAL</b>   | Other   |
| <b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>                                     | 0 V   |
| <b>PRODUCT CATEGORY</b>   | Accessories   |
| <b>VOLTAGE TYPE</b>   | AC  |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                                      | 70 °C   |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                                      | -25 °C  |
| <b>CONTINUITY RESISTOR</b>  | 0 mΩ  |
| <b>NOMINAL CURRENT</b>  | 0 A   |
| <b>CABLE LENGTH</b>   | 2 m   |
| <b>CABLE SHEATH MATERIAL</b>  | Other   |
| <b>DEGREE OF PROTECTION</b>   | Other   |
| <b>COLOR CABLE SHEATH</b>   | Yellow  |
| <b>ELECTRICAL CONNECTION TYPE (BOX-SIDED)</b>                                   | Other   |
| <b>ELECTRICAL CONNECTION TYPE (FIELD-SIDED)</b>                                 | M12   |
| <b>CONTACT BODY MATERIAL</b>  | Other   |
| <b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MAX</b> | 70 °C   |
| <b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MIN</b> | 40 °C   |
| <b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING)</b>               | 70 °C   |

## Resources

|                        |  |
|------------------------|--|
| <b>CATALOGUES</b>      | <a href="#">Product Range Catalog</a><br><a href="#">Sensors – products, basic information, applications</a> |
| <b>DRAWINGS</b>        | <a href="#">eaton-proximity-switches-csds-connecting-cable-3d-drawing.eps</a>                                |
| <b>MULTIMEDIA</b>      | <a href="#">We make what matters</a>   |
| <b>WIRING DIAGRAMS</b> | <a href="#">eaton-proximity-switches-csas-connecting-cable-wiring-diagram.eps</a>                            |

|   |              |
|---|--------------|
| <b>- MAX</b>  |              |
| <b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING)</b> | 40 °C        |
| <b>- MIN</b>  |              |
| <b>PLUG-IN CONTACT TYPE (BOX-SIDED)</b>                           | Male (plug)  |
| <b>PLUG-IN CONTACT TYPE (FIELD-SIDED)</b>                         | Female (bus) |
| <b>POSITIONING CABLE FEED (BOX-SIDED)</b>                         | Other        |
| <b>POSITIONING CABLE FEED (FIELD-SIDED)</b>                       | Straight     |

|                        |
|------------------------|
| <b>PROJECT NAME:</b>   |
| <b>PROJECT NUMBER:</b> |
| <b>PREPARED BY:</b>    |
| <b>DATE:</b>           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

