

# Specifications

## Eaton 136275

Eaton Moeller® series CSDR Connection cable, 4p/3Ltg, DC current, coupling m12 angled, open end, L=5m CSDR4A3CY2205-LP

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series CSDR Accessory Connection cable
<b>CATALOG NUMBER</b>	136275
<b>MODEL CODE</b>	CSDR4A3CY2205-LP
<b>EAN</b>	4015081330676
<b>PRODUCT LENGTH/DEPTH</b>	190.5 mm
<b>PRODUCT HEIGHT</b>	25.4 mm
<b>PRODUCT WIDTH</b>	190.5 mm
<b>PRODUCT WEIGHT</b>	0.52 kg
<b>CERTIFICATIONS</b>	CE



Powering Business Worldwide

## Product specifications

<b>TYPE</b>	Connecting cables
<b>NUMBER OF POLES</b>	Four-pole
<b>CABLE TYPE</b>	Multi-core Coupling, angled, Input side Cable end, open, Output side
<b>CONTACT SURFACE MATERIAL</b>	Other
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	0 V
<b>PRODUCT CATEGORY</b>	Accessories
<b>VOLTAGE TYPE</b>	DC
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>CONTINUITY RESISTOR</b>	0 mΩ
<b>NOMINAL CURRENT</b>	0 A
<b>CABLE LENGTH</b>	5 m
<b>CABLE SHEATH MATERIAL</b>	Other
<b>DEGREE OF PROTECTION</b>	Other
<b>COLOR CABLE SHEATH</b>	Yellow
<b>ELECTRICAL CONNECTION TYPE (BOX-SIDED)</b>	Other
<b>ELECTRICAL CONNECTION TYPE (FIELD-SIDED)</b>	M12
<b>CONTACT BODY MATERIAL</b>	Other
<b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MAX</b>	70 °C
<b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MIN</b>	40 °C
<b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING)</b>	70 °C

## Resources

<b>CATALOGUES</b>	<a href="#">Product Range Catalog</a> <a href="#">Sensors – products, basic information, applications</a>
<b>DRAWINGS</b>	<a href="#">eaton-proximity-switches-csdr-connecting-cable-3d-drawing.eps</a>
<b>MULTIMEDIA</b>	<a href="#">We make what matters</a>
<b>WIRING DIAGRAMS</b>	<a href="#">eaton-proximity-switches-csdr-connecting-cable-wiring-diagram-002.eps</a>

<b>- MAX</b>	
<b>PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING) - MIN</b>	40 °C
<b>PLUG-IN CONTACT TYPE (BOX-SIDED)</b>	Male (plug)
<b>PLUG-IN CONTACT TYPE (FIELD-SIDED)</b>	Female (bus)
<b>POSITIONING CABLE FEED (BOX-SIDED)</b>	Other
<b>POSITIONING CABLE FEED (FIELD-SIDED)</b>	Angled

<b>PROJECT NAME:</b>
<b>PROJECT NUMBER:</b>
<b>PREPARED BY:</b>
<b>DATE:</b>



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

