Specifications

Eaton 136293

Eaton Moeller® series CSDS Connection cable, 4p, DC current, coupling M12 flat, plug M12 flat, L=3m

S
Eaton Moeller® series CSDS Accessory Connection cable
136293
CSDS4A4CY2203-D
4015081330812
177.8 mm
25.4 mm
152.4 mm
0.27 kg
CE



Product specifications	
ТҮРЕ	Connecting cables
NUMBER OF POLES	Four-pole
CABLE TYPE	Multi-core Coupling, straight, Input side Plug, straight, Output side
CONTACT SURFACE MATERIAL	Other
RATED OPERATIONAL VOLTAGE (UE) - MAX	0 V
PRODUCT CATEGORY	Accessories
VOLTAGE TYPE	DC
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CONTINUITY RESISTOR	0 mΩ
NOMINAL CURRENT	0 A
CABLE LENGTH	3 m
CABLE SHEATH MATERIAL	Other
DEGREE OF PROTECTION	Other
COLOR CABLE SHEATH	Yellow
ELECTRICAL CONNECTION TYPE (BOX-SIDED)	M12
ELECTRICAL CONNECTION TYPE (FIELD-SIDED)	M12
CONTACT BODY MATERIAL	Other
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MAX	70 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MIN	40 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING)	70 °C

Resources	
CATALOGUES	Product Range Catalog Sensors – products, basic information, applications
DRAWINGS	eaton-proximity-switches- csds-connecting-cable-3d- drawing-002.eps
MULTIMEDIA	We make what matters
WIRING DIAGRAMS	eaton-proximity-switches- csdr-connecting-cable- wiring-diagram-003.eps

- MAX	
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING) - MIN	40 °C
PLUG-IN CONTACT TYPE (BOX-SIDED)	Male (plug)
PLUG-IN CONTACT TYPE (FIELD-SIDED)	Female (bus)
POSITIONING CABLE FEED (BOX-SIDED)	Straight
POSITIONING CABLE FEED (FIELD-SIDED)	Straight

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









