

Specifications

Photo is representative

Eaton 136315

Eaton Moeller® series CSDR Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=3m

General specifications

PRODUCT NAME	Eaton Moeller® series CSDR Accessory Connection cable
CATALOG NUMBER	136315
MODEL CODE	CSDR4A4CY2203-D
EAN	4015081330973
PRODUCT LENGTH/DEPTH	165.1 mm
PRODUCT HEIGHT	12.7 mm
PRODUCT WIDTH	165.1 mm
PRODUCT WEIGHT	0.09 kg
CERTIFICATIONS	CE

Product specifications

TYPE	Connecting cables
NUMBER OF POLES	Four-pole
CABLE TYPE	Plug, angled, Output side Multi-core Coupling, straight, Input side
CONTACT SURFACE MATERIAL	Other
RATED OPERATIONAL VOLTAGE (UE) - MAX	0 V
PRODUCT CATEGORY	Accessories
VOLTAGE TYPE	DC
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CONTINUITY RESISTOR	0 mΩ
NOMINAL CURRENT	0 A
CABLE LENGTH	3 m
CABLE SHEATH MATERIAL	Other
DEGREE OF PROTECTION	Other
COLOR CABLE SHEATH	Yellow
ELECTRICAL CONNECTION TYPE (BOX-SIDED)	M12
ELECTRICAL CONNECTION TYPE (FIELD-SIDED)	M12
CONTACT BODY MATERIAL	Other
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MAX	70 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MIN	40 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING)	70 °C

Resources

CATALOGUES	Product Range Catalog Sensors – products, basic information, applications
DRAWINGS	eaton-proximity-switches-csdr-connecting-cable-3d-drawing-002.eps
MULTIMEDIA	We make what matters
WIRING DIAGRAMS	eaton-proximity-switches-csdr-connecting-cable-wiring-diagram-003.eps

- MAX	
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING)	40 °C
- MIN	
PLUG-IN CONTACT TYPE (BOX-SIDED)	Male (plug)
PLUG-IN CONTACT TYPE (FIELD-SIDED)	Female (bus)
POSITIONING CABLE FEED (BOX-SIDED)	Angled
POSITIONING CABLE FEED (FIELD-SIDED)	Straight

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

