

Specifications



Eaton 138261

Eaton Moeller® series PKE Trip block, 8 - 32 A, Motor protection, Connection to SmartWire-DT: no, For use with: PKE65 basic device

General specifications

PRODUCT NAME	Eaton Moeller® series PKE Trip block
CATALOG NUMBER	138261
EAN	4015081350414
PRODUCT LENGTH/DEPTH	84.4 mm
PRODUCT HEIGHT	69.9 mm
PRODUCT WIDTH	55 mm
PRODUCT WEIGHT	0.196 kg
CERTIFICATIONS	CSA-C22.2 No. 14-10 VDE 0660 UL CSA File No.: 165628 CE IEC/EN 60947 IEC/EN 60947-4-1 CSA Class No.: 3211-05 CSA UL 508 UL File No.: E36332 UL Category Control No.: NLRV
CATALOG NOTES	This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures.
MODEL CODE	PKE-XTUW-32

Features & Functions

FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Motor protection Overload release Motor protection for heavy starting duty
NUMBER OF POLES	Three-pole

General

CURRENT FLOW TIMES - MIN	500 (Class 5) AC-4 cycle operation, Main conducting paths 700 (Class 10) AC-4 cycle operation, Main conducting paths 1000 (Class 20) AC-4 cycle operation, Main conducting paths Note: Going below the minimum current flow time can cause overheating of the load (motor). 900 (Class 15) AC-4 cycle operation, Main conducting paths For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.
---------------------------------	---

CUT-OUT PERIODS - MIN	≤ 500 ms, main conducting paths, AC-4 cycle operation
DEGREE OF PROTECTION	Device: IP20 Terminals: IP00
OPERATING FREQUENCY	60 Operations/h
OVERLOAD RELEASE CURRENT SETTING - MIN	8 A
OVERLOAD RELEASE CURRENT SETTING - MAX	32 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Accessories
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
TEMPERATURE COMPENSATION	-25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660
VOLTAGE TYPE	Self powered

Ambient conditions, mechanical

SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
-------------------------	---

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED FREQUENCY - MIN	50 Hz
RATED FREQUENCY - MAX	60 Hz
RATED OPERATIONAL CURRENT (IE)	32 A
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	32 A
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	690 V
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	690 V

Switching capacity

SWITCHING CAPACITY AT AC-3 (UP TO 690 V)	32 A
---	------

Short-circuit rating

SHORT-CIRCUIT RELEASE	± 20% tolerance, Trip blocks Trip block fixed 15.5 x I _r Delayed approx. 60 ms, Trip blocks
------------------------------	--

Magnet system

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	0 V
RATED CONTROL SUPPLY	0 V

**VOLTAGE (US) AT AC, 60
HZ - MIN**

**RATED CONTROL SUPPLY
VOLTAGE (US) AT AC, 60
HZ - MAX** 0 V

**RATED CONTROL SUPPLY
VOLTAGE (US) AT DC -
MIN** 0 V

**RATED CONTROL SUPPLY
VOLTAGE (US) AT DC -
MAX** 0 V

Communication

CONNECTION TO SMARTWIRE-DT	No
---------------------------------------	----

Contacts

**NUMBER OF AUXILIARY
CONTACTS (CHANGE-
OVER CONTACTS)** 0

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
CLOSED CONTACTS)** 0

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
OPEN CONTACTS)** 0

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID 3.9 W

HEAT DISSIPATION CAPACITY PDISS 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID 1.3 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 32 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

10.2.2 CORROSION RESISTANCE Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements.

10.5 PROTECTION AGAINST ELECTRIC SHOCK Does not apply, since the entire switchgear needs to be evaluated.

Resources

BROCHURES [eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf](#)

[eaton-motor-protective-circuit-breaker-pke-and-communication-modul-pke-brochure-w12107613en-en-us.pdf](#)

CATALOGUES [Product Range Catalog Switching and protecting motors](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

CHARACTERISTIC CURVE [eaton-manual-motor-starters-pke65-characteristic-curve-005.eps](#)

[DA-DC-00004545.pdf](#)

[DA-DC-00004969.pdf](#)

[DA-DC-00005031.pdf](#)

[DA-DC-00004950.pdf](#)

DECLARATIONS OF CONFORMITY [DA-DC-00005037.pdf](#)

[DA-DC-00004944.pdf](#)

[DA-DC-00005002.pdf](#)

[DA-DC-00004945.pdf](#)

[DA-DC-00004244.pdf](#)

DRAWINGS [eaton-manual-motor-starters-pke-trip-block-3d-drawing.eps](#)

[eaton-manual-motor-starters-mounting-3d-drawing.eps](#)

ECAD MODEL [ETN.138261.edz](#)

INSTALLATION INSTRUCTIONS [IL034013ZU](#)

INSTALLATION VIDEOS [WIN-WIN with push-in technology](#)

[Video Motor Protective Circuit Breaker PKE](#)

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

MANUALS AND USER GUIDES	eaton-motor-protection-pke12-32-65-mn03402004z-de-de-en-us.pdf
MCAD MODEL	DA-CS-pke_xtu65 DA-CD-pke_xtu65
SALES NOTES	eaton-pke-modbus-rtu-modul-flyer-fl034008en-en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

