

Specifications



Eaton 138388

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar adapter, 4p, for NZM2, 250A, UL508

General specifications

PRODUCT NAME	Eaton xEffect SASY 60i MCCB adapter
CATALOG NUMBER	138388
MODEL CODE	NZM2-4-XAD250
EAN	4015081351688
PRODUCT LENGTH/DEPTH	35 mm
PRODUCT HEIGHT	270 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	1.8 kg
COMPLIANCES	RoHS conform
GLOBAL CATALOG	138388

Product specifications

USED WITH	NZM2(-4), PN2(-4), N2(-4)
TYPE	<ul style="list-style-type: none"> 60 mm system Busbar adapters for NZM
FEATURES	Self-extinguishing acc. UL 94
ADAPTER WIDTH	140 mm
BUSBAR ADAPTER WIDTH	140 mm
BUSBAR DISTANCE	60 mm
BUSBAR THICKNESS - MAX	10 mm
BUSBAR THICKNESS - MIN	5 mm
NOMINAL CURRENT	250 A
RAIL WIDTH	30 mm
VOLTAGE RATING AT AC	690 V AC
NUMBER OF POLES	Four-pole
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	200 A
ELECTRIC CONNECTION TYPE	Other
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	8.1 W
CREEPAGE RESISTANCE	CTI 200
FUNCTIONS	Busbar adapters for NZM Component adapter for circuit breakers and switch-disconnector
TEMPERATURE RESISTANCE	Up to 120 °C
MOUNTING RAIL ARMAMENT	None
RATED OPERATION CURRENT (IE)	250 A
SUITABLE FOR	Surface mounting on flat copper busbars 12 – 30 x 5 – 10, double T and triple T profile

Resources

BROCHURES	eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf
CATALOGS	Product Range Catalog Switching and protecting motors
CERTIFICATION REPORTS	eaton-xeffect-sasy-60i-declaration-of-conformity.pdf
DRAWINGS	eaton-control-panels-xeffect-sasy-busbar-adapter-dimensions-002.eps eaton-control-panels-xeffect-sasy-busbar-adapter-3d-drawing.eps
INSTALLATION INSTRUCTIONS	eaton-nzm2-4-xad250-instruction-leaflet-il123020zu.pdf
TECHNICAL DATA SHEETS	eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

