

1400775

https://www.phoenixcontact.com/us/products/1400775

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Valve connector BI (11 mm), Wiring: Z diode, cable length: 3 m

Commercial data

Item number	1400775
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF07
Product key	BF1DMA
GTIN	4046356511520
Weight per piece (including packing)	122.4 g
Weight per piece (excluding packing)	114.9 g
Customs tariff number	85444290
Country of origin	PL



1400775

https://www.phoenixcontact.com/us/products/1400775

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	3
No. of cable outlets	1

Electrical properties

Nominal voltage U _N	24 V AC
	24 V DC

Mechanical properties

Mechanical data

Signaling

Status display	1 LED
Status display present	Yes

Connector

Connection 1

Туре	Plug straight M12
Coding type	A
Connection 2	

Cable/line

Туре

Cable length	3 m
Cable length	3 111

PUR halogen-free black [PUR]

Dimensional drawing



Valve connector BI (11 mm)

Cable weight	30 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]



1400775

https://www.phoenixcontact.com/us/products/1400775

Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	3x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm (Signal line)
External cable diameter	4.50 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	min. 20 MΩ*km
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 1200 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	22.5 mm
Smallest bending radius, movable installation	45 mm
Max. bending cycles	15000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	according to DIN VDE 0482
	According to DIN EN 50265-2-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	largely oil-resistant
	partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Ambient temperature (operation)	-40 °C 80 °C (cable, fixed installation)
	-20 °C 80 °C (Cable, flexible installation)



1400775

https://www.phoenixcontact.com/us/products/1400775

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1400775



Œ.	CSAus Approval ID: 13631				
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		24 V	4 A	-	-



1400775

https://www.phoenixcontact.com/us/products/1400775

Classifications

ECLASS

	ECLASS-11.0	27060312		
	ECLASS-12.0	27060312		
	ECLASS-13.0	27060312		
ETIM				
	ETIM 8.0	EC001855		
UNSPSC				
	UNSPSC 21.0	31251500		



1400775

https://www.phoenixcontact.com/us/products/1400775

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes			
Exemption	7(c)-l			
China RoHS				
Environment friendly use period (EFUP)	EFUP-50			
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.			
EU REACH SVHC				
REACH candidate substance (CAS No.)	Diboron trioxide(CAS: 1303-86-2)			
	Lead monoxide (lead oxide)(CAS: 1317-36-8)			



1400775

https://www.phoenixcontact.com/us/products/1400775

Accessories

SAC-V-SCREW-M3-29 KNURL - Screw

1403779

https://www.phoenixcontact.com/us/products/1403779



Fillister head screw with plastic knurl, M3 x 40

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com