

SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423  
<https://www.phoenixcontact.com/us/products/1402423>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 17-pos., PUR/PVC, RAL 9005 (black), shielded, straight M12 SPEEDCON male plug (A-coded) to straight M12 SPEEDCON female plug, cable length: 20 m

Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1402423       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF03          |
| Product key                          | BF1CNA        |
| GTIN                                 | 4046356615433 |
| Weight per piece (including packing) | 2,172 g       |
| Weight per piece (excluding packing) | 2,142.6 g     |
| Customs tariff number                | 85444290      |
| Country of origin                    | DE            |

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Number of positions  | 17                    |
| No. of cable outlets | 1                     |
| Shielded             | yes                   |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | V0                                          |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuZn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | PA 6.6                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |         |
|-----------------------|---------|
| Nominal voltage $U_N$ | 30 V AC |
|                       | 30 V DC |
| Nominal current $I_N$ | 1.5 A   |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Connector

#### Connection 1

|                     |                            |
|---------------------|----------------------------|
| Type                | Plug straight M12 SPEEDCON |
| Number of positions | 17                         |
| Locking type        | SPEEDCON                   |
| Coding type         | A                          |

#### Connection 2

|                     |                              |
|---------------------|------------------------------|
| Type                | Socket straight M12 SPEEDCON |
| Number of positions | 17                           |
| Locking type        | SPEEDCON                     |
| Coding type         | A                            |

### Cable/line

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

|                                               |                                                                                                                                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable length                                  | 20 m                                                                                                                                            |
| Black PUR/PVC twisted pair [35T]              |                                                                                                                                                 |
| Dimensional drawing                           |                                                               |
| Cable weight                                  | 105 kg/km                                                                                                                                       |
| UL AWM Style                                  | 20233 / 1061 (80°C/300 V)                                                                                                                       |
| Number of positions                           | 17                                                                                                                                              |
| Shielded                                      | yes                                                                                                                                             |
| Cable type                                    | Black PUR/PVC twisted pair [35T]                                                                                                                |
| Conductor structure signal line               | 18x 0.10 mm                                                                                                                                     |
| AWG signal line                               | 26                                                                                                                                              |
| Conductor cross section                       | 17x 0.14 mm <sup>2</sup> (Signal line)                                                                                                          |
| Wire diameter incl. insulation                | 1 mm ±0.05 mm (Signal line)                                                                                                                     |
| External cable diameter                       | 9.20 mm ±0.2 mm                                                                                                                                 |
| Outer sheath, material                        | PUR                                                                                                                                             |
| External sheath, color                        | black RAL 9005                                                                                                                                  |
| Conductor material                            | Tin-plated Cu litz wires                                                                                                                        |
| Material wire insulation                      | PVC                                                                                                                                             |
| Single wire, color                            | white-brown, green-yellow, gray-pink, blue-red, black-violet, gray/pink-red/blue, white/green-brown/green, white/yellow-yellow/brown-white/gray |
| Overall twist                                 | 7 pairs and 1 three-way unit, intertwisted                                                                                                      |
| Optical shield covering                       | 85 %                                                                                                                                            |
| Max. conductor resistance                     | 142 Ω/km (at 20 °C)                                                                                                                             |
| Insulation resistance                         | ≥ 10 MΩ*km (at 20 °C)                                                                                                                           |
| Nominal voltage, cable                        | 42 V AC                                                                                                                                         |
| Test voltage                                  | 1500 V AC                                                                                                                                       |
| Minimum bending radius, fixed installation    | 5 x D                                                                                                                                           |
| Minimum bending radius, flexible installation | 10 x D                                                                                                                                          |
| Smallest bending radius, fixed installation   | 46 mm                                                                                                                                           |
| Smallest bending radius, movable installation | 92 mm                                                                                                                                           |
| Max. bending cycles                           | 4000000                                                                                                                                         |
| Flame resistance                              | According to DIN EN 60332-1-2<br>According to VW-1                                                                                              |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                                                                                             |
| Other resistance                              | hydrolysis and microbe resistant (in accordance with EN 50396)                                                                                  |
| Special properties                            | Flexible cable conduit capable                                                                                                                  |
| Ambient temperature (operation)               | -30 °C ... 80 °C (cable, fixed installation)                                                                                                    |

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423  
<https://www.phoenixcontact.com/us/products/1402423>

|  |                                                |
|--|------------------------------------------------|
|  | -5 °C ... 80 °C (Cable, flexible installation) |
|--|------------------------------------------------|

## Environmental and real-life conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient conditions              |                                  |
| Degree of protection            | IP65                             |
|                                 | IP67                             |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423  
<https://www.phoenixcontact.com/us/products/1402423>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1402423>

|  <b>UL Listed</b><br>Approval ID: FILE E 221474 | Nominal voltage U <sub>N</sub> | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|----------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|-------------------|-------------------------------|
|                                                                                                                                  | 30 V                           | 1 A                            | -                 | -                             |

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423  
<https://www.phoenixcontact.com/us/products/1402423>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## Accessories

### PROT-M12 FS-PA-CHAIN - Sealing cap

1430873

<https://www.phoenixcontact.com/us/products/1430873>

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 plugs



---

### SAC-M12-EXCLIP-M - Locking clip

1558988

<https://www.phoenixcontact.com/us/products/1558988>

Locking clip for the pin side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## UCT-WMT (23X4) - Conductor marker

0801453

<https://www.phoenixcontact.com/us/products/0801453>



Conductor marker, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 30

---

## UC-WMT (23X4) - Conductor marker

0819411

<https://www.phoenixcontact.com/us/products/0819411>



Conductor marker, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 24

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## US-WMT (23X4) - Cable marker

0828769

<https://www.phoenixcontact.com/us/products/0828769>



Cable marker, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 56

---

## WMTW (23X4)R - Cable marker

0831004

<https://www.phoenixcontact.com/us/products/0831004>



Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 3000

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## PROT-M12 MS-PA-CHAIN - Screw plug

1430899

<https://www.phoenixcontact.com/us/products/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



---

## SAC-M12-EXCLIP-F - Locking clip

1558991

<https://www.phoenixcontact.com/us/products/1558991>

Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

## TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

---

## TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

# SAC-17P-MS/20,0-35T/FS SH SCO - Sensor/actuator cable



1402423

<https://www.phoenixcontact.com/us/products/1402423>

## SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)