

VS-M12FSBP-IP20-94B-LI/0,3 - Network cable



1403267

<https://www.phoenixcontact.com/pc/products/1403267>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled Ethernet cable, shielded, 4-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), M12 flush-type socket, rear/screw mounting with M16 thread to RJ45 plug/IP20, line, length: 0.3 m

Commercial data

Item number	1403267
Packing unit	1 pc
Minimum order quantity	50 pc
Product key	ABQDGI
GTIN	4046356646215
Weight per piece (including packing)	50 g
Weight per piece (excluding packing)	48.1 g
Customs tariff number	85444210
Country of origin	PL

VS-M12FSBP-IP20-94B-LI/0,3 - Network cable



1403267

<https://www.phoenixcontact.com/pc/products/1403267>

Technical data

Product properties

Product type	Data cable preassembled
Number of positions	8
Shielded	yes

Electrical properties

Transmission characteristics (category)	Class D
Wave impedance	100 Ω

Material specifications

Outer sheath, material	PUR
Conductor material	Bare Cu litz wires

Cable/line

Cable type	Ethernet
Cable structure	4x2xAWG26/7; S/FTP
External cable diameter	6.40 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Wire diameter incl. insulation	1 mm
Single wire, color	white-blue, white-orange, white-green, white-brown
Cable cross section	0.14 mm ²
Conductor material	Bare Cu litz wires
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Wave impedance	100 Ω $\pm$ 15 % (at 1 ... 100 MHz)
Smallest bending radius, fixed installation	min. 32 mm (cable, fixed installation)
Smallest bending radius, movable installation	min. 32 mm (Cable, flexible installation)
Ambient temperature (operation)	-25 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	Plug / socket
	-40 °C ... 80 °C (without mechanical actuation)
	-25 °C ... 80 °C (Cable, flexible installation)

VS-M12FSBP-IP20-94B-LI/0,3 - Network cable



1403267

<https://www.phoenixcontact.com/pc/products/1403267>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1403267>



EAC

Approval ID: 19060508

VS-M12FSBP-IP20-94B-LI/0,3 - Network cable



1403267

<https://www.phoenixcontact.com/pc/products/1403267>

Classifications

ECLASS

ECLASS-11.0	27060307
ECLASS-12.0	27060307
ECLASS-13.0	27060307

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	591fc2c7-bb56-4623-ba3a-5dc51bedb1aa