

# HC-ADV-B16-HHWH-1SGM32-PL - Housing



1404232

<https://www.phoenixcontact.com/sk/products/1404232>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B16, with screw locking, material: PA, cable outlets: 1, lateral, M32, height: 95 mm, cable gland: with, Standard

## Your advantages

- Integrated screw connection
- Lower costs than metal version
- Low weight
- Lower risk of condensation

## Commercial data

Item number	1404232
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF7
Product key	BF7APG
Catalog page	Page 616 (C-2-2019)
GTIN	4046356682039
Weight per piece (including packing)	164.6 g
Weight per piece (excluding packing)	160 g
Customs tariff number	85389099
Country of origin	DE

# HC-ADV-B16-HHWH-1SGM32-PL - Housing



1404232

<https://www.phoenixcontact.com/sk/products/1404232>

## Technical data

### Notes

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, M, K, HV06-I-PR, HV 6-E...C
---------	---


### Product properties

Product type	Housing with screw locking
Application	Standard
Type	B16
No. of cable outlets	1
Type of the screw connection	M32
Fixing screws	M6 (screw head: 5 mm Allen screw)
Housing type	Sleeve housing
Shielded	no
Cable outlet	lateral
Pg screw connection	with

### Connection data

External cable diameter	11 mm ... 21 mm
Tightening torque	3 Nm ... 5 Nm (for M6 mounting screws on the sleeve housing)
Tightening torque, union nut	7.50 Nm

### Dimensions

Dimensional drawing	
Width	57 mm
Height	95 mm
Length	126 mm
Wrench size, union nut	30 mm

### Installation dimensions

Width of the assembly cutout	35 mm
Length of the assembly cutout	86 mm

### Material specifications

Material Pressure screw	PA
Flammability rating according to UL 94	V0 (Housing)
Seal material Profile gasket	NBR
Seal material Cable seal	NBR
Housing material	PA

# HC-ADV-B16-HHWH-1SGM32-PL - Housing



1404232

<https://www.phoenixcontact.com/sk/products/1404232>

Locking latch material	Stainless steel
Material of locking screw	Stainless steel
Impact strength	IK08

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 100 °C

## Mechanical properties

### Mechanical data

Type of the screw connection	M32
Locking type	Screw

## Cable/line


External cable diameter (Cable 1)	11 mm ... 21 mm
-----------------------------------	-----------------

## Mounting

Assembly instructions	M6 locking screw, with 5 mm Allen screw head
Fixing screws	M6 (screw head: 5 mm Allen screw)

## Drawings

Dimensional drawing




Mounting cutout

1) when M4 screws are used

2) when self-tapping Torx® screws are used (Torx® 20, M4)

Dimensional drawing



Dimensional drawing

# HC-ADV-B16-HHWH-1SGM32-PL - Housing




1404232

<https://www.phoenixcontact.com/sk/products/1404232>


## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sk/products/1404232>

**DNV**  
Approval ID: TAE000037S

**EAC**  
Approval ID: RU C-DE.BL08.B.00511

**cUL Recognized**  
Approval ID: E255026

**UL Recognized**  
Approval ID: E255026

**cULus Recognized**

# HC-ADV-B16-HHWH-1SGM32-PL - Housing



1404232

<https://www.phoenixcontact.com/sk/products/1404232>

## Classifications

### ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

### ETIM

ETIM 9.0	EC000437
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

# HC-ADV-B16-HHWH-1SGM32-PL - Housing



1404232

<https://www.phoenixcontact.com/sk/products/1404232>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT s.r.o.  
Námestie Mateja Korvína 1  
811 07 Bratislava  
+421 2 3210 1470  
[obchod.sk@phoenixcontact.com](mailto:obchod.sk@phoenixcontact.com)