


HC-HV06-I-CT-M - Contact insert

1405262

<https://www.phoenixcontact.com/no/products/1405262>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert, number of positions: 6+2+PE, size: B16, power contacts: 6, control contacts: 2, number of connections per position: 1, Pin, Crimp connection, 690 V, 16 A, 0.5 mm² ... 4 mm²

Commercial data

Item number	1405262
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	31BBF
Product key	BF7ABG
Catalog page	Page 561 (C-2-2019)
GTIN	4055626063508
Weight per piece (including packing)	67.86 g
Weight per piece (excluding packing)	46.6 g
Customs tariff number	85389099
Country of origin	CN

HC-HV06-I-CT-M - Contact insert

1405262

<https://www.phoenixcontact.com/no/products/1405262>



Technical data

Notes

General	For HC ADVANCE-B16, HC-HV 6 housings, crimp contacts CK 2,5-ED (crimp contacts not included in scope of supply)
General	Connectors may be operated only when there is no load/voltage.

Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
-----------------------	---


Product properties

Type	B16 B32
Product type	Contact insert with a fixed no. of positions
Number of positions	8
Connection profile	6+2+PE
Number of connections per position	1
No. of power contacts	6
No. of control contacts	2
Contact material type	turned
Series	HC-HV

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Dimensions

Dimensional drawing	
Width	34 mm
Height	32 mm
Length	84 mm
Drill hole distance, horizontal	77.5 mm
Drill hole distance, vertical	27 mm

Mechanical characteristics

Contact diameter	2.5 mm
------------------	--------

Connection data

Connection technology

Connection technology	Crimp connection
-----------------------	------------------

HC-HV06-I-CT-M - Contact insert



1405262

<https://www.phoenixcontact.com/no/products/1405262>

	Crimp connection
Number of connections per position	1
Conductor connection	
Conductor cross section	0.5 mm ² ... 4 mm ² (power contacts)
	0.5 mm ² ... 4 mm ² (control contacts)
Connection cross section AWG	20 ... 12 (power contacts)
	20 ... 12 (control contacts)
Tightening torque	0.8 Nm ... 1.2 Nm (PE connection)
	0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)
Stripping length of the individual wire	7.5 mm (Power)
	7.5 mm (Signal)

Electrical properties

Rated voltage (III/2) contacts	830 V
Rated voltage (III/3)	690 V
	690 V
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	6 kV
Rated surge voltage	8 kV (power contacts)
	6 kV (control contacts)
Rated current	16 A (power contacts)
	16 A (control contacts)

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PC
Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
---------------------------------	--

Standards and regulations

Testing

HC-HV06-I-CT-M - Contact insert



1405262

<https://www.phoenixcontact.com/no/products/1405262>

Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---


HC-HV06-I-CT-M - Contact insert



1405262
<https://www.phoenixcontact.com/no/products/1405262>


Drawings

Diagram



Derating diagram

Dimensional drawing



Dimensional drawing


HC-HV06-I-CT-M - Contact insert



1405262

<https://www.phoenixcontact.com/no/products/1405262>

Schematic diagram



Connector pin assignment


HC-HV06-I-CT-M - Contact insert

1405262

<https://www.phoenixcontact.com/no/products/1405262>



Dimensional drawing



Mounting cutout when used without housing

HC-HV06-I-CT-M - Contact insert

1405262

<https://www.phoenixcontact.com/no/products/1405262>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/no/products/1405262>

DNV Approval ID: TAE000037S				
---------------------------------------	--	--	--	--

CSA Approval ID: 013631_6233_01				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	600 V	20 A	20 - 12	-

EAC Approval ID: RU C-DE.BL08.B.00511				
---	--	--	--	--

cULus Recognized Approval ID: E468743				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	600 V	16 A	- 12	-

HC-HV06-I-CT-M - Contact insert



1405262

<https://www.phoenixcontact.com/no/products/1405262>

Classifications

ECLASS

ECLASS-11.0	27440205
ECLASS-12.0	27440205
ECLASS-13.0	27440205

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

HC-HV06-I-CT-M - Contact insert



1405262

<https://www.phoenixcontact.com/no/products/1405262>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com