

SAC-12P-100,0-35T/SH-0,14 - Cable reel



1405789

<https://www.phoenixcontact.com/pc/products/1405789>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



By the meter, Cable reel, shielded, PUR/PVC, black RAL 9005, 12-wire, color single wire: white-brown, green-yellow, gray-pink, blue-red, black-violet, gray/pink-red/blue, cable length: 100 m, Twisted pair cable

Commercial data

Item number	1405789
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BF1LAA
Catalog page	Page 303 (C-2-2019)
GTIN	4046356768078
Weight per piece (including packing)	9,040 g
Weight per piece (excluding packing)	9,040 g
Customs tariff number	85444995
Country of origin	DE

SAC-12P-100,0-35T/SH-0,14 - Cable reel

1405789

<https://www.phoenixcontact.com/pc/products/1405789>

Technical data


Product properties

Product type	Cable by the meter
Number of positions	12
Application	Connector
Shielded	yes

Cable/line

Cable length	100 m
--------------	-------

Black PUR/PVC twisted pair [35T]

Dimensional drawing	
Cable weight	87 kg/km
UL AWM Style	20233 / 1061 (80°C/300 V)
Number of positions	12
Shielded	yes
Cable type	Black PUR/PVC twisted pair [35T]
Conductor structure signal line	18x 0.10 mm
AWG signal line	26
Conductor cross section	12x 0.14 mm ² (Signal line)
Wire diameter incl. insulation	1 mm ±0.05 mm (Signal line)
External cable diameter	8.50 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Tin-plated Cu litz wires
Material wire insulation	PVC
Single wire, color	white-brown, green-yellow, gray-pink, blue-red, black-violet, gray/pink-red/blue
Twisted pairs	2 cores to the pair
Overall twist	Six pairs around the filler to the core
Optical shield covering	85 %
Max. conductor resistance	≤ 142 Ω/km (at 20 °C)
Insulation resistance	≥ 10 MΩ*km (at 20 °C)
Nominal voltage, cable	42 V AC
Test voltage	1500 V AC
Minimum bending radius, fixed installation	5 x D

SAC-12P-100,0-35T/SH-0,14 - Cable reel



1405789

<https://www.phoenixcontact.com/pc/products/1405789>

Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	43 mm
Smallest bending radius, movable installation	85 mm
Max. bending cycles	2000000
Flame resistance	According to DIN EN 60332-1-2
	According to VW-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	hydrolysis and microbe resistant (in accordance with EN 50396)
Special properties	Flexible cable conduit capable
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

SAC-12P-100,0-35T/SH-0,14 - Cable reel



1405789

<https://www.phoenixcontact.com/pc/products/1405789>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1405789>

 UL Listed Approval ID: FILE E 221474	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	1 A	-	-

SAC-12P-100,0-35T/SH-0,14 - Cable reel



1405789

<https://www.phoenixcontact.com/pc/products/1405789>

Classifications

ECLASS

ECLASS-11.0	27061801
ECLASS-12.0	27061801
ECLASS-13.0	27061801

ETIM

ETIM 9.0	EC003249
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-12P-100,0-35T/SH-0,14 - Cable reel



1405789

<https://www.phoenixcontact.com/pc/products/1405789>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com