

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 8-position, PE-X halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on free cable end, cable length: 10 m, for outdoor applications, with high-grade steel knurl

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Robust throughout: resistant to oil, UV, and ozone, withstands temperatures from -40°C ... +105°C

Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1407273                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | BF1CFA                         |
| Catalog page                         | Page 157 (C-4-2013)            |
| GTIN                                 | 4046356773911                  |
| Weight per piece (including packing) | 627 g                          |
| Weight per piece (excluding packing) | 627 g                          |
| Customs tariff number                | 85444290                       |
| Country of origin                    | PL                             |

# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | External areas        |
| Number of positions  | 8                     |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Insulation characteristics

|                     |   |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

### Material specifications

|                                        |                 |
|----------------------------------------|-----------------|
| Flammability rating according to UL 94 | V0              |
| Material of grip body                  | PP              |
| Contact material                       | CuSn            |
| Contact surface material               | Ni/Au           |
| Contact carrier material               | PP              |
| Material for screw connection          | Stainless steel |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 30 V AC                    |
|                       | 30 V DC                    |
| Nominal current $I_N$ | 2 A                        |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

### Connector

#### Connection 1

|                     |                   |
|---------------------|-------------------|
| Type                | Plug straight M12 |
| Number of positions | 8                 |

# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

|             |   |
|-------------|---|
| Coding type | A |
|-------------|---|

## Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

## Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|

## PE-X black [28X]

|                                               |                                                                                    |
|-----------------------------------------------|------------------------------------------------------------------------------------|
| Dimensional drawing                           |  |
| Cable weight                                  | 65 kg/km                                                                           |
| Number of positions                           | 8                                                                                  |
| Shielded                                      | no                                                                                 |
| Cable type                                    | PE-X black [28X]                                                                   |
| Conductor structure signal line               | 32x 0.10 mm                                                                        |
| AWG signal line                               | 24                                                                                 |
| Conductor cross section                       | 8x 0.25 mm <sup>2</sup>                                                            |
| Wire diameter incl. insulation                | 1.17 mm ±0.02 mm                                                                   |
| External cable diameter                       | 6.80 mm ±0.2 mm                                                                    |
| Outer sheath, material                        | PE-X                                                                               |
| External sheath, color                        | black-gray RAL 7021                                                                |
| Conductor material                            | Bare Cu litz wires                                                                 |
| Material, filler                              | PP yarn                                                                            |
| Material wire insulation                      | PE-X                                                                               |
| Single wire, color                            | white, brown, green, yellow, gray, pink, blue, red                                 |
| Thickness, insulation                         | approx. 0.25 mm (Core insulation)                                                  |
| Thickness, outer sheath                       | approx. 1.30 mm                                                                    |
| Overall twist                                 | 8 wires around filler to the core                                                  |
| Length of twist, overall twist                | 67 mm                                                                              |
| Max. conductor resistance                     | ≤ 78 Ω/km (at 20 °C)                                                               |
| Insulation resistance                         | ≥ 100 MΩ*km (at 20 °C)                                                             |
| Nominal voltage, cable                        | ≤ 300 V AC                                                                         |
| Test voltage                                  | ≥ 3000 V AC (Spark test)                                                           |
| Minimum bending radius, fixed installation    | 5 x D                                                                              |
| Minimum bending radius, flexible installation | 10 x D                                                                             |
| Smallest bending radius, fixed installation   | 34 mm                                                                              |
| Smallest bending radius, movable installation | 68 mm                                                                              |
| Max. bending cycles                           | 2000000                                                                            |

# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

|                                                 |                                                                                                                                                   |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Minimum bending radius, drag chain applications | 10 x D                                                                                                                                            |
| Traversing path                                 | 10 m                                                                                                                                              |
| Traversing rate                                 | 3 m/s                                                                                                                                             |
| Acceleration                                    | 10 m/s <sup>2</sup>                                                                                                                               |
| Halogen-free                                    | in accordance with DIN VDE 0472 part 815<br>in accordance with DIN EN 50267-2-1                                                                   |
| Flame resistance                                | According to DIN EN 60332-1-2<br>according to DIN EN 50266-2-5                                                                                    |
| Resistance to oil                               | According to DIN EN 60811-2-1, 168 h at 100°C<br>According to DIN EN 50306                                                                        |
| Other resistance                                | Resistance to fuels (according to IEC 60811, 168 h at 70°C)<br>UV resistant (according to DIN VDE 0276-605)                                       |
| Special properties                              | Irradiated                                                                                                                                        |
| Ambient temperature (operation)                 | -40 °C ... 105 °C (cable, fixed installation)<br>-15 °C ... 105 °C (Cable, flexible installation)<br>20 °C ±5 °C (cable, drag chain applications) |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Degree of protection            | IP65<br>IP67<br>IP68<br>IP69K                                                                                          |
| Ambient temperature (operation) | -40 °C ... 105 °C (Plug / socket)<br>-40 °C ... 85 °C (On sudden changes in temperature (according to IEC 60512-11-4)) |


## Standards and regulations

### M12

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |


## Drawings

Schematic diagram



Pin assignment M12 plug, 8-pos., A-coded, view plug side

Circuit diagram




# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

Dimensional drawing



Plug, M12 x 1, straight, shielded

# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1407273>

### DNV

Approval ID: TAE00002K4



### EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387

# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-8P-M12MS/10,0-28X OD - Sensor/actuator cable



1407273

<https://www.phoenixcontact.com/pc/products/1407273>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)